



VN330SP(8932)


QUAD HIGH SIDE SMART POWER SOLID STATE RELAY

General Features

Type	$V_{\text{demag}}^{(*)}$	$R_{\text{DSon}}^{(*)}$	$I_{\text{out}}^{(*)}$	V_{CC}
VN330SP(8932)	$V_{\text{CC}}-55\text{V}$	$0.32\Omega^{(**)}$	1A	36V

(*)Per channel.

(**)at $T_J = 85\text{ }^\circ\text{C}$



Features

- OUTPUT CURRENT : 1A PER CHANNEL
- DIGITAL INPUT CLAMPED AT 32V MINIMUM VOLTAGE
- SHORTED LOAD AND OVER-TEMPERATURE PROTECTIONS
- BUILT-IN CURRENT LIMITER
- UNDERVOLTAGE SHUT-DOWN
- OPEN DRAIN DIAGNOSTIC OUTPUT
- FAST DEMAGNETIZATION OF INDUCTIVE LOADS

Description

The VN330SP(8932) is a monolithic device made using STMicroelectronics VIPower Technology, intended for driving four independent resistive or inductive loads with one side connected to ground. Active current limitation avoids dropping the system power supply in case of shorted load. Built-in thermal shut-down protects the chip from overtemperature and short circuit. The open drain diagnostic output indicates over-temperature conditions.

Block Diagram




Table 1. Absolute Maximum Rating

Symbol	Parameter	Value	Unit
V_{CC}	Power supply voltage	45	V
$-V_{CC}$	Reverse supply voltage	-0.3	V
I_{OUT}	Output current (continuous)	Internally limited	A
I_R	Reverse output current (per channel)	-6	A
I_{IN}	Input current (per channel)	± 10	mA
I_{DIAG}	Diag pin current	± 10	mA
V_{ESD}	Electrostatic discharge (R = 1.5KW; C = 100pF)	2000	V
E_{AS}	Single pulse avalanche energy per channel not simultaneously <i>Figure 3.</i>	400	mJ
P_{tot}	Power dissipation at $T_C \leq 25^\circ\text{C}$	Internally limited	W
T_J	Junction operating temperature	Internally limited	$^\circ\text{C}$
T_{stg}	Storage Temperature	-55 to 150	$^\circ\text{C}$

Figure 1. Connection Diagram (Top View)




Figure 2. Current and Voltage Conventions




Table 2. Thermal data

Symbol	Parameter		Max Value	Unit
R _{thJC}	Thermal resistance junction-case (<i>Note:1</i>)	Max	2	°C/W
R _{thJA}	Thermal resistance junction-ambient (<i>Note:2</i>)	Max	50	°C/W

Note: 1.Per channel

Note: 2.When mounted using minimum recommended pad size on FR-4 board

Electrical Characteristics (10V < V_{CC} < 36V; -25°C < T_J < 125°C; unless otherwise specified)

Table 3. Power Section

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
V _{CC}	Supply voltage		10		36	V
R _{ON}	On state resistance	I _{OUT} = 0.5A; T _J = 125°C I _{OUT} = 0.5A; T _J = 85°C I _{OUT} = 0.5A; T _J = 25°C			0.4 0.32 0.2	Ω Ω Ω
I _S	Supply current	All channels OFF; V _{IN} = 30V; On state; T _J = 125°C I _{OUT1...I_{OUT4}} = 0V			1 10	mA mA
V _{demag}	Output voltage at turn-off	I _{OUT} = 0.5A; L _{LOAD} >= 1mH	V _{CC} -65	V _{CC} -55	V _{CC} -45	V

Table 4. Logical Input

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
V _{IL}	Input low level voltage				2	V
V _{IH}	Input high level voltage .	<i>Note:3</i>	3.5			V
V _{I(HYST)}	Input hysteresis voltage			0.5		V
I _{IN}	Input current	V _{IN} = 0 to 30V V _{IN} = 0 to 2V	25		600	μA μA
I _{LGND}	Output current in ground disconnection	V _{CC} = V _{INn} = GND = DIAG = 24V; T _J = 25°C			25	mA
V _{ICL}	Input clamp voltage <i>Note:3</i>	I _{IN} = 1mA I _{IN} = -1mA	32	36 -0.7		V V

Note: 3.The input voltage is internally clamped at 32V minimum, it is possible to connect the input pins to an higher voltage via an external resistor calculate to not exceed 10mA

Table 5. Switching ($V_{CC} = 24V$)

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
$t_{d(ON)}$	Turn-on delay time of Output current	$I_{OUT} = 0.5A$, Resistive Load Input rise time $< 0.1\mu s$, $T_J = 25^\circ C$ $T_J = 125^\circ C$		30	40 60	μs μs
t_r	Rise time of Output current	$I_{OUT} = 0.5A$, Resistive Load Input rise time $< 0.1\mu s$, $T_J = 25^\circ C$ $T_J = 125^\circ C$		50	100 115	μs μs
$t_{d(OFF)}$	Turn-off delay time of Output current	$I_{OUT} = 0.5A$, Resistive Load Input rise time $< 0.1\mu s$, $T_J = 25^\circ C$ $T_J = 125^\circ C$		20	30 40	μs μs
t_f	Fall time of Output current	$I_{OUT} = 0.5A$, Resistive Load Input rise time $< 0.1\mu s$, $T_J = 25^\circ C$ $T_J = 125^\circ C$		8	15 20	μs μs
$(di/dt)_{on}$	Turn-on current slope	$I_{OUT} = 0.5A$, $I_{OUT} = I_{LIM}$, $T_J = 25^\circ C$			0.5 2	A/ μs A/ μs
$(di/dt)_{off}$	Turn-off current slope	$I_{OUT} = 0.5A$, $I_{OUT} = I_{LIM}$, $T_J = 25^\circ C$			2 4	A/ μs A/ μs

Table 6. Protections

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
$V_{DIAG}^{(*)}$	Status voltage output low	$I_{DIAG} = 5mA$ (Fault condition)			1	V
$V_{SCL}^{(*)}$	Status clamp voltage	$I_{DIAG} = 1mA$	32	36		V
		$I_{DIAG} = -1mA$		-0.7		V
V_{USD}	Undervoltage shut down		5		8	V
I_{LIM}	DC Short circuit current	$V_{CC} = 24V; R_{LOAD} < 10m\Omega$	1		2.5	A
I_{OVPK}	Peak short circuit current	$V_{CC} = 24V; V_{IN} = 30; R_{LOAD} < 10m\Omega$			4	A
I_{DIAGH}	Leakage on diag pin in high state	$V_{DIAG} = 24V$			100	μA
I_{LOAD}	Output leakage current	$V_{CC} = 10$ to $36V; V_{IN} = V_{IL}$ 4 Channels in Parallel			25	μA
t_{SC}	Delay time of current limiter				100	μs
T_{TSD}	Thermal shut down temperature		150	170		$^{\circ}C$
T_R	Thermal reset temperature		135	155		$^{\circ}C$

(*)Status determination > 100ms after the switching edge.

Note: If INPUT pin is floating the corresponding channel will automatically switch OFF. If GND pin is disconnected, the channel will switch OFF provided VCC not exceed 36V.

Figure 3. Avalance Energy Test Circuit




Figure 4. Peak Short Circuit Test Diagram




Table 7. Truth Table

Conditions	INPUTn	OUTPUTn	Diagnostic
Normal operation	L	L	H
	H	H	H
Overtemperature	L	L	H
	H	L	L
Undervoltage	L	L	H
	H	L	H
Shorted load (Current limitation)	L	L	H
	H	H	H

Figure 5. Switching Waveforms




Figure 6. Switching Parameter Test Conditions





Figure 7. Driving Circuit



PowerSO-10™ Thermal Data

Figure 8. PowerSO-10™ PC Board




Figure 9. R_{thJA} Vs. PCB copper area in open box free air condition




Table 8. PowerSO-10™ Mechanical Data

Symbol	millimeters		
	Min	Typ	Max
A	3.35		3.65
A (*)	3.4		3.6
A1	0.00		0.10
B	0.40		0.60
B (*)	0.37		0.53
C	0.35		0.55
C (*)	0.23		0.32
D	9.40		9.60
D1	7.40		7.60
E	9.30		9.50
E2	7.20		7.60
E2 (*)	7.30		7.50
E4	5.90		6.10
E4 (*)	5.90		6.30
e		1.27	
F	1.25		1.35
F (*)	1.20		1.40
H	13.80		14.40
H (*)	13.85		14.35
h		0.50	
L	1.20		1.80
L (*)	0.80		1.10
a	0°		8°
α (*)	2°		8°

Note: (*) Muar only POA P013P

Figure 10. PowerSO-10™ Package Dimensions




Figure 11. PowerSO-10™ Suggested Pad and Tube Shipment (No Suffix)




Figure 12. Tape and Reel Shipment (Suffix “TR“)




Table 9. Order Codes

Package	Tube	Tape and Reel
PowerSO-10™	VN330SP(8932)	VN330SP(8932)TR

Table 10. Revision History

Date	Revision	Changes
5-Sep-2005	2	New Template. Final release

Information furnished is believed to be accurate and reliable. However, STMicroelectronics assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of STMicroelectronics. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information previously supplied. STMicroelectronics products are not authorized for use as critical components in life support devices or systems without express written approval of STMicroelectronics.

The ST logo is a registered trademark of STMicroelectronics.
All other names are the property of their respective owners

© 2005 STMicroelectronics - All rights reserved

STMicroelectronics group of companies

Australia - Belgium - Brazil - Canada - China - Czech Republic - Finland - France - Germany - Hong Kong - India - Israel - Italy - Japan -
Malaysia - Malta - Morocco - Singapore - Spain - Sweden - Switzerland - United Kingdom - United States of America

www.st.com