


### 3-1546306-0 Product Details



**3-1546306-0**

TE Internal Number: 3-1546306-0

 [Active](#)

 [View 3D PDF](#)

#### Barrier Strips

 [Always EU RoHS/ELV Compliant \(Statement of Compliance\)](#)

#### Product Highlights:

- Barrier Strip
- Barrier Style = Double Row, Dual Barrier
- Block Style = Flat
- 9.53 mm Centerline
- Vertical Mount Angle

[View all Features](#)

#### Documentation & Additional Information

##### Product Drawings:

- [9.50MM \(.374\) DBL ROW BARRIER STRIP W/O WASHER](#) (PDF, English)

##### Catalog Pages/Data Sheets:

- [1-1773458-2 BARRIER STRIPS QUICK REFERENCE GUIDE](#) (PDF, English)

##### Product Specifications:

- None Available

##### Application Specifications:

- None Available

##### Instruction Sheets:

- None Available

##### CAD Files: ([CAD Format & Compression Information](#))

- [2D Drawing](#) (DXF, Version K)
- [3D Model](#) (IGES, Version K)
- [3D Model](#) (STEP, Version K)

[List all Documents](#)

##### Additional Information:

- [Product Line Information](#)

##### Related Products:

- [Tooling](#)

#### Product Features (Please use the Product Drawing for all design activity)

##### Product Type Features:

- [Product Type](#) = Barrier Strip
- [Mount Angle](#) = Vertical
- Screw Material = Steel
- Screw Size = 6-32 x 1/4
- Mounting Ears = With

##### Mechanical Attachment:

- Screw Plating = Nickel
- Mounting Style = Open End Position

##### Electrical Characteristics:

- [Top Hardware](#) = Wire Clamp Combo Head
- Number of Levels = Single
- Current Rating (A) = 20
- Mounting Insert = Without

##### Body Related Features:

- [Barrier Style](#) = Double Row, Dual Barrier
- [Block Style](#) = Flat
- [Centerline \(in \[mm\]\)](#) = 0.375 [9.53]
- Number of Positions = 30
- Length (mm [in]) = 302.00 [11.890]
- Block Material = Thermoplastic
- Block Color = Black
- Wire Range (mm [AWG]) = 0.30-3.00<sup>2</sup> [22-12]

##### Contact Related Features:

- Mounting Options = End Mounting Ears

##### Industry Standards:

- [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- [Lead Free Solder Processes](#) = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C
- RoHS/ELV Compliance History = Always was RoHS compliant

##### Other:

- Brand = Buchanan
- Comment = Other options available upon request, consult our Product Information Center.