

### 61117-1 Product Details



TE Internal Number: 61117-1



View 3D PDF

### .200" Centerline, 250 V, 13 A max.



Always EU RoHS/ELV Compliant (Statement of

Compliance)

#### **Product Highlights:**

- Commercial MATE-N-LOK Product Line
- Contact
- Contact Type = Socket
- Crimp Termination Method to Wire/Cable
- Pre-Tin Contact Plating, Mating Area, Material

View all Features

#### **Documentation & Additional Information**

#### **Product Drawings:**

COMMERCIAL MATE-N-LOK (PDF, English)

#### Catalog Pages/Data Sheets:

- REPRESENTATIVE TERMINALS AND CONNECTORS (PDF, English)
- SOFT SHELL PIN SOCKET CONNECTORS STANDARD DENSITY (PDF, English)

#### Product Specifications:

- Connector, MATE-N-LOK, Commercial (PDF, English)
- Connector, MATE-N-LOK, Commercial (PDF, Japanese)

### **Application Specifications:**

- MATE-N-LOK Commercial Pin And Socket Contacts (PDF, English)
- MATE-N-LOK Commercial Pin and Socket Contacts (PDF, Japanese)

# **Instruction Sheets:**

### CAD Files: (CAD Format & Compression Information)

- 2D Drawing (DXF, Version AC)
- 3D Model (IGES, Version AC)
- 3D Model (STEP, Version AC)

## **Additional Information:**

## **Related Products:**

- Tooling
- Housings (70)

List all Documents

## Product Features (Please use the Product Drawing for all design activity)

### **Product Type Features:**

- Product Line = Commercial MATE-N-LOK
- Product Type = Contact
- Termination Method to Wire/Cable = Crimp
- Wire/Cable Type = Discrete Wire
- Industry Application = Standard, TMWIRE2BOARD, RAILWAYPRODS, TMPOWERP, TESTANDMEASURE

# **Electrical Characteristics:**

- Contact Current Rating (A) = 13
- Operating Voltage Reference = AC
- Operating Voltage (VAC) = 250

### **Body Related Features:**

- Wire Range (mm [AWG]) =  $0.50-2.00^2$  [20-14]
- Contact Diameter (mm [in]) = 2.13 [0.084]

# **Contact Related Features:**

- Contact Type = Socket
- Contact Plating, Mating Area, Material = Pre-Tin
- Contact Base Material = Brass

## **Industry Standards:**

- RoHS/ELV Compliance = RoHS compliant, ELV compliant
- <u>Lead Free Solder Processes</u> = Not relevant for lead free
- RoHS/ELV Compliance History = Always was RoHS compliant

## Conditions for Usage:

- Accepts Wire Insulation Diameter, Range (mm [in]) = 2.54 3.30 [0.100 0.130]
- Applies To = Wire

# Packaging Related Features:

Packaging Method = Strip

# Other:

- Brand = AMP
- Comment = HDM Applicator part number ending in -1 is used on AMPOMATOR CLS Machine with T or G terminators, -2 used on AMP-O-LECTRIC Model K Machine; -3,-4, or -6 is used on AMP-O-LECTRIC Model G Machine.