


REV.	DATE	DESCRIPTION
A	03/18/05	UPDATE DRAWING FORMAT
B	05/09/06	MODIFY STRIPPING DIMENSIONS, MATERIAL AND PLATING



NO.	DESCRIPTION	MATERIAL	FINISH	QTY	DO NOT SCALE DRAWING	APPROVALS	DATE	PART DESCRIPTION	PART NO.	DWG. NO.	REV.	SIZE	SCALE
8								<p>Amphenol Connex</p> <p>TNC R/A CRIMP PLUG (FOR RG-316/U DOUBLE BRAID CABLE)</p>	122407	122407.DWG	B	A	NA
7													
6	FERRULE	BRASS	NICKEL	1									
5	NUT	BRASS	NICKEL	1									
4	CONTACT PIN	BRASS	GOLD	1									
3	INSULATOR	TEFLON	NATURAL	1									
2	HOUSING/SHELL	BRASS	NICKEL	1									
1	DESCRIPTION	MATERIAL	FINISH	QTY									

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN MILLIMETERS. DIMENSIONS IN [] ARE IN INCHES AND FOR CUSTOMER REFERENCE ONLY. TOLERANCES FOR MILLIMETERS ARE:
0.5 - 8mm ± 0.20mm
8 - 30mm ± 0.40mm
30 - 120mm ± 0.50mm
UNLESS OTHERWISE SPECIFIED, TOLERANCES FOR INCHES ARE:
.020 - .315 = ± 0.007"
.315 - 1.180 = ± 0.015"
1.180 - 4.724 = ± 0.020"

CAD FILE C:/122/1224007.DWG