

REV.		DATE	DESCRIPTION	
A		01/12/02	MODIFY FERRULE LENGTH	

RECOMMENDED CABLE STRIPPING DIM'S.

RECOMMENDED MOUNTING HOLE

#10-32UNF-2A

DESCRIPTION	MATERIAL	FINISH	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETERS DIMENSIONS IN [] ARE IN INCHES FOR CUSTOMER REFERENCE ONLY		APPROVALS		DATE	TITLE			
1	BODY	BRASS	GOLD		DRAWN	G.R.S.	01/12/02	MMCX BULKHEAD CRIMP JACK (FOR RG-178B/u, 196A/u CABLE)			
2	INSULATOR	TEFLON	NATURAL		CHECKED						
3	BARREL	BRASS	GOLD		ISSUED						
4	CONTACT PIN	BER. COPPER	GOLD	UNLESS OTHERWISE SPECIFIED TOLERANCES FOR INCHES ARE: .XXX = ± 0.005" .XX = ± 0.010" .X = ± 0.020"				SIZE			
5	FERRULE	COPPER	GOLD					FSCM NO.			
6								99001			
7										DWG. NO.	
8										262120.DWG	
								SCALE		NA	
								PART NO.		262120	
								SHEET		1 OF 1	
										REV.	
										A	