



- NOTE:**
- ITEM No. 1 & 5 MUST WITHSTAND MIN 10 in-lbs TORQUE WITHOUT ROTATING WITHIN ITEM No. 6
 - ITEM No. 1 & 5 MUST ISOLATED FROM ITEM No. 6
 - IMPEDANCY: 75 OHM
 - FREQUENCY RANGE: DC-3GHz

ITEM	PART No.	DWG No.	DESCRIPTION	QTY
8	HN16-1/2-28X28	HN16-1/2-28X28	16 HEX NUT	01
7	LW-16/13X05	LW-16/13X05	LOCK WASHER	02
6	B7925-6-C	B7925-6-C	HOUSING	01
5	A000410-1-B	A000410-1-B	BODY	01
4	B7925-4-A	B7925-4-A	INSULATOR	01
3	B7900-4	B7900-4	CONTACT PIN	01
2	B7996ZZ-3T-75	B7996ZZ-3T-75	INSULATOR	02
1	B7925-1-B	B7925-1-B	BODY	01

UNLESS OTHERWISE SPECIFIED TOLERANCE TO BE:

LINEAR	ANGULAR
X ± 0.50	X' ± 1'
X.X ± 0.20	X'X' ± 30'
X.XX ± 0.10	X'X'X' ± 15'

THIS DOCUMENT IS THE PROPERTY OF AMPHENOL AUSTRALIA PTY. LTD.. NO PART THEREOF MAY BE REPRODUCED AND USED WITHOUT THE PRIOR WRITTEN CONSENT OF THE OWNER

CAD FILE: 55010085100110 DRN: M.N.H. DATE: 14-09-10

REV: 0 FIRST ISSUE M.N.H. 14-09-10

CHANGE DETAILS BY DATE CHG/No

SCALE: 2:1 UOS PART No AC-BNC-PJA-75 SIZE: A3

TITLE: BNC PUSH-JACK ISOLATED ADAPTOR 75 Ohm

Amphenol
Amphenol Australia Pty Ltd, 2 Finways Blvd, Kingsborough, VIC 3173

DRAWING NO. 55010085-100-1 SHEET 1 OF 1

1 2 3 4 5 6