



TWINAXIAL ADAPTERS

| Cable/ Description | Dimensions, inches (millimeters) | | | | Notes | | | Mtg. Hole | IBM Ref. Number | Amphenol Number | Fig. |
|-------------------------------|----------------------------------|------------|-------------|------------|-------|------|------|--------------|--------------------|--------------------|------|
| | a | b | c | e | CAI | Pit. | Ins. | | | | |
| Bulkhead Jack to Jack Adapter | 1.67 (42.4) | .945 (ø24) | 1.32 (33.6) | .217 (5.5) | — | P7 | D25 | Y | — | 7925-RFX | 1 ▲ |
| Tee Adapter Jack-Jack-Jack | 1.93 (49) | 1.46 (37) | 1.08 (27.5) | — | — | P15 | D25 | — | 68-51167 | 82-5677-RFX | 2 ▲ |
| Barrel Adapter, Jack-Jack | 1.67(42.4) | .768(19.5) | — | — | — | P1 | D12 | — | — | 82-5588 | 3 ▲ |
| Barrel Adapter, Jack-Jack | 1.67(42.4) | .768(19.5) | — | — | — | P7 | D25 | — | — | 82-5588-RFX | 3 ▲ |
| Tee Adapter Jack-Plug-Jack | 1.93 (49) | 1.77 (45) | 1.40 (35.5) | — | — | P15 | D25 | — | 4178269 | 26850-RFX | 4 ▲ |

● accommodates cable diameter ▲ Distributor stocked