

Recommended PCB Layout (top view)

Materials and Finish

Housing Material-
 PBT Thermoplastic
 UL 94V-0 Rated
 Color: Black

Design meets UL 1863 Sec. 8
 Electrical Probe and Sec. 20
 Child Finger test requirements

Contact Material-
 Phosphor Bronze

Contact Plating Options-
 Standard: 0.0001" Nickel
 Underplating, Selectively Plated
 0.00015" Gold on Contact Area,
 Tin Plated on Termination End

-50 Option: 0.0001" Nickel Underplating,
 Selectively Plated 0.000050"
 Gold on Contact Area to
 Comply with FCC Requirements
 Under No. 47 C.F.R. Part 68,
 Subpart F, Tin Plated on
 Termination End

Electrical Characteristics

Current Rating-
 1.5 Amps

Voltage Rating-
 125V DC

Insulation Resistance-
 500 Megohms Min.

Dielectric Withstanding Voltage-
 1000V rms, 60Hz

Contact Resistance-
 20 milliohms Max.

Operating Temperature-
 -40°C to +85°C

Part Number	Contact Area Plating Finish
GDX-A-66	15u" Gold (standard)
GDX-A-66-50	50u" Gold (-50 option)




Tolerances
X.X ± 0.25
X.XX ± 0.15
Unless Stated Otherwise

REV.	DATE	DESCRIPTION	REV. BY	CHK. BY	DRAWN BY	DATE
A1	5/17/05	New Drawing	H. MA	C. Furumasa	H. MA	5/17/05
A2	05/13/10	ECO #10-025	S. Vien	H. MA		

GDX-A-66-xx

RA PCB Mount Mod Jack, RoHS Compliant
 0.595" Height, 6 positions, 6 contacts



UNITS
mm