

PLC-BSP- 24DC/21-21

Order No.: 2912439



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2912439>

14 mm PLC basic terminal blocks with spring-cage connection method, input voltage 24 V DC (without relay or optocoupler)



Commercial data	
GTIN (EAN)	4 046356 050845
sales group	G211
Pack	10 pcs.
Customs tariff	85364190

Product notes

WEEE/RoHS-compliant since:
03/03/2006

<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data	
Input data	
Nominal input voltage U_N	24 V DC
Status display	LED
Protective circuit	Protection against polarity reversal Polarity protection diode

Connection data

Conductor cross section solid min.	0.14 mm ²
Conductor cross section solid max.	2.5 mm ²
Conductor cross section stranded min.	0.14 mm ²
Conductor cross section stranded max.	2.5 mm ²
Conductor cross section AWG/kcmil min.	26
Conductor cross section AWG/kcmil max	14
Connection method	Spring-cage connection
Stripping length	8 mm

General data

Width	14 mm
Height	80 mm
Depth	94 mm
Color	green
Ambient temperature (operation)	-40 °C ... 60 °C
Ambient temperature (storage/transport)	-40 °C ... 85 °C
Operating mode	100% operating factor
Inflammability class acc. to UL 94	V0
Mounting position	Any
Assembly instructions	In rows with zero spacing

Certificates / Approvals



Certification

CUL Listed, GL, UL Listed

Additional products

Item	Designation	Description
General		
2982100	OPT-24DC/ 24DC/ 5	Pluggable miniature optocouplers, power optocouplers, input: 24 V DC, output: 3-33 V DC/5 A

2982171	OPT-24DC/230AC/ 2	Pluggable miniature optocouplers, power optocouplers, input: 24 V DC, output: 24-253 V AC/ 2 A
2961192	REL-MR- 24DC/21-21	Pluggable miniature relays, with power contact, 2 PDT, input voltage 24 V DC
2961215	REL-MR- 24DC/21-21AU	Pluggable miniature relays, with multi-layer contact, 2 PDT, input voltage 24 V DC

Address

PHOENIX CONTACT Inc., USA
586 Fulling Mill Road
Middletown, PA 17057, USA
Phone (800) 888-7388
Fax (717) 944-1625
<http://www.phoenixcon.com>



© 2011 Phoenix Contact
Technical modifications reserved;