


IB IL TEMP CON UTH


Order No.: 2819312



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2819312>

Inline temperature regulators, without accessories, 8 inputs for thermocouples, 8 outputs, 24 V DC, 2-wire connection method

Commercial data

GTIN (EAN)	4  017918 951016
Note	Made-to-order
sales group	K413
Pack	1 pcs.
Customs tariff	85389091

<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data

Interfaces

Interface	Inline local bus
Connection method	Inline data jumper

Power supply

Typical current consumption	250 mA
Max. current consumption	4 A

Electrical isolation

Test section	5 V supply, incoming remote bus/7.5 V supply (bus logics) 500 V AC 50 Hz 1 min
--------------	--

	5 V supply, outgoing remote bus/7.5 V supply (bus logics) 500 V AC 50 Hz 1 min
	7.5 V supply (bus logics)/24 V supply (I/O) 500 V AC 50 Hz 1 min
	24 V supply (I/O) / functional earth ground 500 V AC 50 Hz 1 min
	Analog inputs/bus logics 500 V AC 50 Hz 1 min
	Analog inputs/24 V supply (I/O) 500 V AC 50 Hz 1 min
	Analog inputs/functional earth ground 500 V AC 50 Hz 1 min

Inputs

Number of inputs	8
Connection method	2-wire
Measured value representation	Depends on thermocouple
Measured value resolution	0.1 K
A/D conversion time	Approx. 70 ms
Sensor types that can be used (TC)	L, J, K, N, S, R, T, C, D, E, B

General data

Degree of protection	IP20
Weight	122 g
Width	48.8 mm
Height	119.8 mm
Depth	71.5 mm
Mounting type	DIN rail
Connection method	Spring-cage connection
	2-wire (shielded)

Certificates / Approvals




Certification	CUL, GOST, UL
Certification Ex:	CUL-EX LIS, UL-EX LIS

Accessories


Item	Designation	Description
Cable/conductor		
2819419	TEMPCON CAB-V24	Interface cable for Inline temperature controllers (IB IL TEMPCON ...), single
Literature		
2698818	IB IL TEMPCON FUNCTION UM	User manual, German, for setting the controller functions of Inline temperature controllers, only available as a download.
2698821	IB IL TEMPCON FUNCTION UM E	User manual, English, for setting the controller functions of Inline temperature controllers, only available as a download.
2698795	IB IL TEMPCON UTH SYS UM	User manual, German, for Inline temperature controllers, only available as a download.
2698805	IB IL TEMPCON UTH SYS UM E	User manual, English, for Inline temperature controllers, only available as a download.
Marking		
0809492	ESL 62X10	Insert strip for laser printer, lettering field: 62 x 10 mm
0809502	ESL 62X46	Insert strip for laser printer, lettering field: 62 x 46 mm
2727501	IB IL FIELD 2	Labeling field, width: 12.2 mm
2727515	IB IL FIELD 8	Labeling field, width: 48.8 mm
Plug/Adapter		
2726337	IB IL SCN-8	Connector, for digital 1, 2 or 8-channel Inline terminals
Software		
2819370	IB IL TEMPCONTROL	License key for using the engineering tools for the multi-channel process controllers of type: IB IL TEMPCON 300, including interface cable TEMPCON CAB-V24. The software must also be downloaded.

Diagrams/Drawings

Connection diagram



Dimensioned drawing



Address

PHOENIX CONTACT Inc., USA
586 Fulling Mill Road
Middletown, PA 17057, USA
Phone (800) 888-7388
Fax (717) 944-1625
<http://www.phoenixcon.com>



© 2011 Phoenix Contact
Technical modifications reserved;