


ME MAX 6,2 SP-TBUS 4-4 KMGY

Order No.: 2869647




<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2869647>

Extra slim electronic housing for DIN rail bus connector, pitch 6.2 mm, 4 connection levels, 8-pos. with spring-cage connection

| Commercial data | |
|--------------------------|--|
| GTIN (EAN) |  4 017918 975142 |
| sales group | F052 |
| Pack | 10 pcs. |
| Customs tariff | 85369010 |
| Catalog page information | Page 617 (CC-2011) |

Product notes

WEEE/RoHS-compliant since:
04/01/2005



<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

| Technical data | |
|------------------|------------------|
| General | |
| Housing type | Complete housing |
| Housing material | PBT |
| Color | light gray |

Dimensions / positions

| | |
|---------------------|---------|
| Length | 93.1 mm |
| Width | 6.2 mm |
| Number of positions | 8 |
| Pitch | 6.2 mm |

Technical data

| | |
|------------------------------------|-------|
| Connection in acc. with standard | CUL |
| Nominal voltage U_N | 300 V |
| Nominal current I_N | 8 A |
| AWG/kcmil | 24-12 |
| Indicator1 | CUL1 |
| Inflammability class acc. to UL 94 | V0 |

Connection data

| | |
|--|---------------------|
| Conductor cross section solid min. | 0.2 mm ² |
| Conductor cross section solid max. | 2.5 mm ² |
| Conductor cross section stranded min. | 0.2 mm ² |
| Conductor cross section stranded max. | 2.5 mm ² |
| Conductor cross section AWG/kcmil min. | 24 |
| Conductor cross section AWG/kcmil max | 12 |
| Stripping length | 8 mm |

Certificates / Approvals



Certification CUL, UL

Accessories

| Item | Designation | Description |
|--------------|---------------|---|
| Tools | | |
| 1204517 | SZF 1-0,6X3,5 | Actuation tool, for ST terminal blocks, also suitable for use as a bladed screwdriver, size: 0.6 x 3.5 x 100 mm, 2-component grip, with non-slip grip |

Address

PHOENIX CONTACT Inc., USA
586 Fulling Mill Road
Middletown, PA 17057, USA
Phone (800) 888-7388
Fax (717) 944-1625
<http://www.phoenixcon.com>



© 2011 Phoenix Contact
Technical modifications reserved;