


IB IL 24 PWR IN/2F-DF-2MBD-PAC

Order No.: 2863834



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2863834>

Inline power terminal block, complete with accessories (connector and labeling field), 24 V DC, with fuse (main and segment voltage) and diagnostics, transmission speed 2 MBaud

Commercial data	
GTIN (EAN)	 4 017918 977733
sales group	K417
Pack	1 pcs.
Customs tariff	85389091
Catalog page information	Page 267 (AX-2009)

Product notes

WEEE/RoHS-compliant since:
07/04/2006



<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data	
Power supply	
Fuse	Safety fuse 5 x 20 with 6.3 A slow
General data	
Weight	44 g

Width	12.2 mm
Height	119.8 mm
Depth	71.5 mm

Inline potential routing

Current consumption from U_L	max. 45 mA DC
Main circuit supply U_M	24 V DC -15% / +20% (in acc. with EN 61131-2) (nominal value)
Power supply at U_M	4 A (nominal value)
Segment supply voltage U_S	24 V DC -15% / +20% (in acc. with EN 61131-2)
Power supply at U_S	4 A (nominal value)

Accessories

Item	Designation	Description
Marking		
0809492	ESL 62X10	Insert strip for laser printer, lettering field: 62 x 10 mm
2727501	IB IL FIELD 2	Labeling field, width: 12.2 mm

Plug/Adapter

2727462	IB IL SCN-PWR IN	Connector, for Inline power and segment terminal blocks
2727637	IB IL SCN-PWR IN-CP	Connector, colored, for Inline power and segment terminal blocks

Address

PHOENIX CONTACT Inc., USA
586 Fulling Mill Road
Middletown, PA 17057, USA
Phone (800) 888-7388
Fax (717) 944-1625
<http://www.phoenixcon.com>



© 2011 Phoenix Contact
Technical modifications reserved;