

ME 22,5 UTG BK

Order No.: 2908427


Illustration shows fully mounted versions of the electronic housing, in green



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2908427>

Lower part of housing closed, fully assembled, with metal foot catch.

Commercial data

GTIN (EAN)	 4 017918 359836
sales group	F050
Pack	100 pcs.
Customs tariff	85472000

Product notes

WEEE/RoHS-compliant since:
04/01/2005



<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Accessories

Item	Designation	Description
Assembly		
2853404	ME 45 UTM GN	Intermediate element for modular extension of the volume of the housing in the pitch. The open intermediate element is 22.5 mm wide.

2853417	ME 45 UTMG GN	Intermediate element for modular extension of the volume of the housing in the pitch. The closed intermediate element is 22.5 mm wide.
2908456	ME B-22,5 MKDSO BK	Filler plugs, for unoccupied terminal points
2908456	ME B-22,5 MKDSO BK	Filler plugs, for unoccupied terminal points
2907143	ME B-22,5 MKDSO GN	Filler plugs, for unoccupied terminal points
2909659	ME B-22,5 MSTBO BK	Filler plugs, for unoccupied terminal points
2906911	ME LPZS	PCB stop, for soldering onto PCB
2906911	ME LPZS	PCB stop, for soldering onto PCB
2908281	ME MF 17,5	Metal foot catch, for intermediate elements.
2853899	ME-SAS	Shield connection clamp for printed circuit terminal block
2853899	ME-SAS	Shield connection clamp for printed circuit terminal block
1707234	MKDSO 2,5/ 4-L	PC terminal block, Nominal current: 24 A, Nom. voltage: 400 V, Pitch: 5 mm, Number of positions: 4, Connection method: Screw connection, Mounting: Soldering, Conductor/PCB connection direction: 0 °, Color: green, Article with lateral pin exit
2869773	MKDSO 2,5/ 4-L BK	PC terminal block, Nominal current: 24 A, Nom. voltage: 400 V, Connection method: Screw connection, Mounting: Soldering, Conductor/PCB connection direction: 0 °, Color: black
1707247	MKDSO 2,5/ 4-R	PC terminal block, Nominal current: 24 A, Nom. voltage: 400 V, Pitch: 5 mm, Number of positions: 4, Connection method: Screw connection, Mounting: Soldering, Conductor/PCB connection direction: 0 °, Color: green, Article with lateral pin exit
2869760	MKDSO 2,5/ 4-R BK	PC terminal block, Nominal current: 24 A, Nom. voltage: 400 V, Connection method: Screw connection, Mounting: Soldering, Conductor/PCB connection direction: 0 °, Color: black

General

2906908	ME LP	PCB, for custom fitting, with contact to DIN rail (EN 60715)
2906908	ME LP	PCB, for custom fitting, with contact to DIN rail (EN 60715)

Plug/Adapter

1734634	CP-MSTB	Keying profile, is inserted into the slot on the plug or inverted header, red insulating material
1734401	CR-MSTB	Coding section, inserted into the recess in the header or the inverted plug, red insulating material
2908294	ME FE-CONTACT	Functional earth ground contact, for intermediate elements.

Address

PHOENIX CONTACT Inc., USA
586 Fulling Mill Road
Middletown, PA 17057, USA
Phone (800) 888-7388
Fax (717) 944-1625
<http://www.phoenixcon.com>



© 2011 Phoenix Contact
Technical modifications reserved;