





# Ring Tongues - Non-Insulated Brazed Seam 16-14 AWG


Product Number <sup>1</sup>	UPC (054007-)	Wire Range (AWG)	Stud Size	W	C	L	E	Thickness	Barrel Length	Barrel I.D.	Terminals per: Carton	Case
M14-2R/SK	01379	16-14	2	0.25	0.22	0.60	0.47	0.030	0.25	0.090	—	1000
M14-4R/SX	49612	16-14	4	0.25	0.22	0.60	0.47	0.030	0.25	0.090	100	500
M14-4R/SK	01380	16-14	4	0.25	0.22	0.60	0.47	0.030	0.25	0.090	—	1000
M14-6R/SX	22294	16-14	6	0.25	0.22	0.60	0.47	0.030	0.25	0.090	100	500
M14-6R/SK	01382	16-14	6	0.25	0.22	0.60	0.47	0.030	0.25	0.090	—	1000
M14-6R/LK	01384	16-14	6	0.31	0.33	0.74	0.58	0.030	0.25	0.090	—	1000
M14-8R/LX	22302	16-14	8	0.31	0.33	0.74	0.58	0.030	0.25	0.090	100	500
M14-8R/LK	13880	16-14	8	0.31	0.33	0.74	0.58	0.030	0.25	0.090	—	1000
M14-10RK	13929	16-14	10	0.33	0.29	0.70	0.54	0.030	0.25	0.090	—	1000
M14-10R/LX	22310	16-14	10	0.31	0.33	0.74	0.58	0.030	0.25	0.090	100	500
M14-10R/LK	01389	16-14	10	0.31	0.33	0.74	0.58	0.030	0.25	0.090	—	1000
M14-14R/SX	22328	16-14	1/4	0.47	0.40	0.89	0.65	0.030	0.25	0.090	100	500
M14-14R/SK	01390	16-14	1/4	0.47	0.40	0.89	0.65	0.030	0.25	0.090	—	1000
M14-516R/SX	49613	16-14	5/16	0.47	0.40	0.89	0.65	0.030	0.25	0.090	100	500
M14-516R/SK	01392	16-14	5/16	0.47	0.40	0.89	0.65	0.030	0.25	0.090	—	1000
M14-38RX	49614	16-14	3/8	0.56	0.40	0.93	0.65	0.030	0.25	0.090	100	500




**M14-2R/S**  
Stud Size: 2  
Wire Range: 16-14




**M14-4R/S**  
Stud Size: 4  
Wire Range: 16-14




**M14-6R/S**  
Stud Size: 6  
Wire Range: 16-14




**M14-6R/L**  
Stud Size: 6  
Wire Range: 16-14




**M14-8R/L**  
Stud Size: 8  
Wire Range: 16-14




**M14-10R**  
Stud Size: 10  
Wire Range: 16-14




**M14-10R/L**  
Stud Size: 10  
Wire Range: 16-14



**M14-14R/S**  
Stud Size: 1/4  
Wire Range: 16-14



**M14-516R/S**  
Stud Size: 5/16  
Wire Range: 16-14



**M14-38R**  
Stud Size: 3/8  
Wire Range: 16-14