Mate	erial			High Conductivity Seamless Copper Tube					
Platin	ng			Electro-Tin					
Wire Size				1/0 AWG			.47 R Ref		
Wire Type				Stranded Copper; Class B: Compact, Compressed or Concentric, Class C: Concentric			Color coded barrel markings		
Wire Strip Length			ı	1.0 in.	.76±.04	NISO OSTR	NING STR COLL COLL / O STR COLL		
Stud Size				3/8 in.	20 2				
UL Listed Wire Connector				Yes, for applications up to 35kv. Consult cable manufacturer for voltage stress relief instructions with applications greater than 2000 volts.	.36±.04	- 1.00±.02	1.00±.02 — .41±.02 DIA (2) PLS		
UL Temperature Rating			90° C						
C.S.A Certified Wire Connector				Yes					
Panduit Color Code on Barrel		ode	PINK						
Panduit Die Index No. on Barrel		x No.	P42	Wire inspection	window —	ndow————————————————————————————————————			
Alternate Industry Die Index No. () on Barrel			У	(12)			.39±.01 .52±.01		
		CE	ERTIFIEC	LISTED Wire Connector	.12±.01				
							CORP. TINLEY PARK, ILLINOI		
0 12	2/02	SAB	DRL	RELEASE	 D	10343	LCD1/0-38D-X Copper Lug - Two-Hole, Standard Barrel		
- '*	_,			1,122,132,		1.55.76	SCALE DRAWING NO / CAD FILE		