



PHYSICAL

Conductors: 28 AWG 7/36 Tinned Copper
 Insulation: .012" PVC, per Color Code Below
 Color Code: WHT, WHT, BLK, GRN, GRN, RED, YEL, YEL & BLU
 Drains: (3) 26 AWG 7/34 Tinned Copper
 Shield: .001" Aluminum/Polyester
 Temperature Rating: 105°C
 Jacket: .030" Nom Black PVC

ELECTRICAL

Impedance: TBD
 Propagation Delay: TBD
 Voltage Rating: 300 V
 Current Rating: 1 A at 10°C Rise Above Ambient
 Insul. Resistance: 10¹⁰ ohms – 10 ft MIN.

All Dimensions in Inches Unless Otherwise Noted

Part Number	Count	A Span, Inches(mm)	C Span (mm)
151-2899-932	9	0.351 (8,92) Nom	0.415 (10,54) Nom

Print Legend

E116273 (UL) 105°C 28AWG CL2

Approvals: UL CL2 105°C and 300 V

REVISION	CHANGES
A	RELEASE - COLOR CODE AND UL
2	REMOVE CU MESH SHIELD, TO AL/POLY
1	DRAFT SPECIFICATION

DRAWN	PROD ENG	QA	MKT	P/ECN#	DRAWING NO. 151-2899-932	AMPHENOL SPECTRA-STRIP 720 SHERMAN AVE TEL (203) 281-3200 HAMDEN CT 06514 FAX (203) 281-5872	Rev A
8/24/06	9/26/06			1056	TITLE: Jacketed, Shielded Planar Cable with 3C (9) Conductor Inner		SHEET 1 of 1