



# Heyclip™ Wire Clips-PVC

## Standard Duty, Adhesive-Backed

- Extruded clip for extra flexibility.
- Made of PVC co-polymer.
- Releasable and reusable clips for easy wire routing.
- Multiple sizes from .187" (4,7 mm) to .750" (19,1 mm) in both light and heavy duty styles.
- Recommended storage temperature from 60°F (16°C) to 80°F (27°C), and approximate relative humidity of 50%.
- Rated static loads apply for parts fastened to a flat, clean, dry surface used within a temperature range of -20°F (-29°C) to 150°F (66°C).
- See page 6-10 for Heyclip Installation Instructions.

MAX. BUNDLE DIAMETER		PART NO. Black	DESCRIPTION	RATED STATIC LOAD (lb.)	PART DIMENSIONS					
in.	mm.				A		B		C	
					in.	mm.	in.	mm.	in.	mm.
.187	4,7	<b>3888</b>	WCA L 187-125	1/8	.50	12,7	.75	19,1	.31	7,9
.250	6,4	<b>3889</b>	WCA L 250-187	3/16	.50	12,7	1.02	25,9	.41	10,4
.375	9,5	<b>3893</b>	WCA L 375-250	1/4	.50	12,7	1.00	25,4	.52	13,2
.500	12,7	<b>3895</b>	WCA L 500-312	5/16	.50	12,7	1.25	31,8	.67	17,0
.625	15,9	<b>3896</b>	WCA L 625-375	3/8	.63	16,0	1.25	31,8	.77	19,6
.750	19,1	<b>3897</b>	WCA L 750-500	1/2	.75	19,1	1.50	38,1	.94	23,9

Standard color black.

## Heavy Duty, Adhesive-Backed

MAX. BUNDLE DIAMETER		PART NO. Black	DESCRIPTION	RATED STATIC LOAD (lb.)	PART DIMENSIONS					
in.	mm.				A		B		C	
					in.	mm.	in.	mm.	in.	mm.
.187	4,7	<b>3898</b>	WCA H 187-250	1/4	1.00	25,4	.75	19,1	.31	7,9
.250	6,4	<b>3899</b>	WCA H 250-375	3/8	1.00	25,4	1.02	25,9	.41	10,4
.375	9,5	<b>3900</b>	WCA H 375-500	1/2	1.00	25,4	1.00	25,4	.52	13,2
.500	12,7	<b>3901</b>	WCA H 500-625	5/8	1.00	25,4	1.25	31,8	.67	17,0
.625	15,9	<b>3902</b>	WCA H 625-750	3/4	1.25	31,8	1.25	31,8	.77	19,6
.750	19,1	<b>3903</b>	WCA H 750-1000	1	1.50	38,1	1.50	38,1	.94	23,9

Standard color black.

