

**Specifications:**

**Military Unit**

|                         |                                   |
|-------------------------|-----------------------------------|
| Sound level Category    | Medium Sound Level                |
| Mode of Operation       | Dual Mode – Fast Pulse/Continuous |
| Mounting                | Panel (see note B)                |
| Voltage Rating          | 6 to 16 Vdc                       |
| Frequency               | 2900 Hz ±500 Hz                   |
| Loudness (Min. Voltage) | 65 dB(A) min. @ 2 FT and 6 Vdc    |
| Loudness (Max Voltage)  | 78 dB(A) min. @ 2FT and 16 Vdc    |
| Current Draw            | 3 mA Max @ 6 Vdc                  |
| Current Draw            | 12 mA Max @ 16 Vdc                |
| Min Pulse Rate (PPS)    | 2 @ 6 Vdc                         |
| Max Pulse Rate (PPS)    | 10 @ 16 Vdc                       |
| Duty Cycle (%)          | 50 (Approx)                       |
| Storage Temperature     | -65°C to +85°C                    |
| Operating Temperature   | -40°C to +85°C                    |
| Weight (Typical)        | 1.6 oz (46 g)                     |
| Housing                 | 6/6 Nylon, Color Black            |
| Options                 | For other options contact factory |

**Dimensions:** Inches (mm)

