



PART No.	L1	SURFACE AREA
R6330-02	4.00	152.16
R6331-02	6.00	209.11
R6332-02	8.00	266.06
R6333-02	10.00	323.01
R6334-02	12.00	379.96
R6335-02	14.00	436.97
R6336-02	16.00	493.87
R6337-02	18.00	515.82
R6338-02	20.00	607.77
R6339-02	25.40	761.54

6	25.294	2557
5	114.87	1081
4	8.286	932
3	12.782	WAS 393 NOW 394
2	5.379	FINISH WAS OTO 919
1	13.1178	
ISS.	DATE	C/N
DRAWN: I.SANDY		
CHECKED: <i>[Signature]</i>		
APPD: <i>[Signature]</i>		
CUSTOMER REF.		
ASSEMBLY DRG:		

MANUFACTURE NOTES:-
 1. 0.30 CHAMFERS FOR LEAD-IN ON THREADS.
 2. REMOVE ALL BURRS.
 3. THREADS TO BE MANUFACTURED IN ACCORDANCE WITH BS3643 PT.2 1981.

HARWIN			TOLERANCES X: ±1mm X.X ±0.25mm X.XX ±0.10mm X.XXX ±0.01mm ANGLES ±1°		MATERIAL: BRASS CZ121 TO BS2874 (BRM1199)		TITLE: M3 STANDARD FEMALE SPACER (5.5mm A/F HEX)		
HARWIN PLC UK TEL: (0705) 370451 FAX: (0705) 324010		HARWIN INC U.S.A. TEL: (812) 285-0055 FAX: (812) 285-0056		HARWIN PTE SINGAPORE TEL: 7794909 FAX: 7793868		FINISH: NICKEL F0203		DRAWING NUMBER: R6330-02 / R6339-02	
IF IN DOUBT - ASK					S/AREA: SEE TABLE mm ²		SHT. 1 OF 1		