


# HEAT SINKS



### HALF BRICK CASE HEATSINK

All Dimensions in mm

<p><b>Vertical Fins</b> P/N: G6620400201 Model No. :M-C308</p> <p>Rca: 3.9°C/W (typ.), At natural convection 1.74°C/W (typ.), At 100LFM 1.33°C/W (typ.), At 200LFM 1.12°C/W (typ.), At 300LFM 0.97°C/W (typ.), At 400LFM</p>	<p><b>Horizontal Fins</b> P/N: G6610120402 Model No. :M-C091</p> <p>Rca: 4.7°C/W (typ.), At natural convection 2.89°C/W (typ.), At 100LFM 2.30°C/W (typ.), At 200LFM 1.88°C/W (typ.), At 300LFM 1.59°C/W (typ.), At 400LFM</p>	<p><b>Horizontal Fins</b> P/N: G6610130402 Model No. :M-C092</p> <p>Rca: 3°C/W (typ.), At natural convection 1.44°C/W (typ.), At 100LFM 1.17°C/W (typ.), At 200LFM 1.04°C/W (typ.), At 300LFM 0.95°C/W (typ.), At 400LFM</p>
------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

### QUARTER BRICK CASE HEATSINK

All Dimensions in mm

<p><b>Vertical Fins</b></p> <p>Rca: 4.78°C/W (typ.), At natural convection 2.44°C/W (typ.), At 100LFM 2.04°C/W (typ.), At 200LFM 1.76°C/W (typ.), At 300LFM 1.58°C/W (typ.), At 400LFM</p>
------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

### FULL BRICK HEATSINK

**Horizontal Fins**  
P/N: G6620090204  
Model No. :M-B012

All Dimensions in mm

Thermal pad: SR60x115.8x0.23 (G6135013070)  
Screw SMP+SW M3x8L (75A1300322)  
Thermal Resistance: 2.07°C/W (typ.), At natural convection

### HALF BRICK HEATSINK ASSEMBLY

Screw  
Washer  
Heatsink  
Heat-PAD

Heat Sink: M-C308 (G6620400201)  
M-C091 (G6610120402)  
M-C092 (G6610130402)  
Thermal Pad: S256.9x60x0.25mm (G6135041091)  
Screw: SMP+SW M3x8L (G75A1300322)

All Specifications Typical At Nominal Line, Full Load and 25°C Unless Otherwise Noted.