




## Heyco® Vent Plugs

- Permits the passage of air for ventilation and heat dissipation.
- Convex, matte finish head tapers to a thin edge.
- Multiple sizes for use in .500" (12,7 mm) to 4.00" (101,6 mm) diameter holes.
- VP-500 through VP-875 have 3/32" (2,4 mm) diameter vent holes. All other sizes have 1/8" (3,2 mm) diameter vents.
- Locks firmly into panel up to .250" (6,4 mm) thick.
- Quick and easy installation with only fingertip pressure.

PANEL DIMENSIONS				PART NO.		DESCRIPTION	No. of Vent Holes	PART DIMENSIONS			
Maximum Thickness		Mounting Hole Diameter		Black	White			A Head Diameter		B Overall Height	
in.	mm.	in.	mm.				in.	mm.	in.	mm.	
.125	3,2	.500	12,7	<b>2637</b>	<b>2638</b>	VP-500	4	.578	14,7	.406	10,3
.125	3,2	.625	15,8	<b>2657</b>	<b>2658</b>	VP-625	5	.734	18,7	.406	10,3
.125	3,2	.750	19,1	<b>2677</b>	<b>2678</b>	VP-750	8	.906	23,0	.406	10,3
.125	3,2	.812	20,6	<b>2688</b>	<b>2689</b>	VP-812	8	.890	22,6	.406	10,3
.125	3,2	.875	22,2	<b>2697</b>	<b>2698</b>	VP-875	9	1.015	25,8	.453	11,5
.125	3,2	1.000	25,4	<b>2707</b>	<b>2708</b>	VP-1000	9	1.203	30,6	.453	11,5
.125	3,2	1.093 1.125	27,8 - 28,6	<b>2726</b>	<b>2727</b>	VP-1093	9	1.218	30,9	.453	11,5
.125	3,2	1.187	30,2	<b>2736</b>	<b>2737</b>	VP-1187	10	1.312	33,3	.453	11,5
.125	3,2	1.250	31,8	<b>2743</b>	<b>2744</b>	VP-1250	10	1.375	34,9	.453	11,5
.125	3,2	1.250	31,8	<b>2797</b>	—	SVP-1250	4	1.375	34,9	.453	11,5
.125	3,2	1.375	34,9	<b>2756</b>	<b>2757</b>	VP-1375	11	1.500	38,1	.453	11,5
.125	3,2	1.500	38,1	<b>2766</b>	<b>2767</b>	VP-1500	13	1.671	42,4	.453	11,5
.125	3,2	1.750	44,5	<b>2776</b>	<b>2777</b>	VP-1750	13	1.906	48,4	.453	11,5
.125	3,2	2.000	50,8	<b>2786</b>	<b>2787</b>	VP-2000	19	2.140	54,4	.468	11,9
.250	6,4	2.500	63,5	<b>2793</b>	<b>2794</b>	VP-2.5	19	2.718	69,0	.750	19,1
.250	6,4	3.000	76,2	<b>2458</b>	<b>2459</b>	VP-3.0	26	3.171	80,5	.750	19,1
.250	6,4	3.500	88,9	<b>2467</b>	<b>2468</b>	VP-3.5	38	3.656	92,9	.750	19,1
.250	6,4	4.000	101,6	<b>2476</b>	<b>2477</b>	VP-4.0	48	4.156	105,6	.750	19,1

Standard color black. Consult Heyco for other colors.  
 Locking fingers in fractional increments up to the maximum chassis thickness.  
 Approximate Head Thickness: .063" (1,6 mm). Thickness may vary.



*Quick Specs*

Material	6/6 Nylon
Certifications	Recognized under the Component Program of Underwriters' Laboratories, File E51579 Certified by Canadian Standards Association, File LR8919
Flammability Rating	94V-2
Material Temperature Index	257°F (125°C)—Maximum temperature on part not to exceed 221°F (105°C)