
THIS DOCUMENT CONTAINS DATA PROPRIETARY TO PROJECTS UNLIMITED, INC. ANY USE OR REPRODUCTION. IN ANY FORM, WITHOUT PRIOR WRITTEN PERMISSION OF PROJECTS UNLIMITED, INC. IS PRCHIBITED.


© 2005, Projects Unlimited Inc.


SPECIFICATIONS

PARAMETERS	VALUES	UNITS
DIRECTIVITY	OMNI	-
SENSITIVITY	-38±2	dB
STANDARD OPERATING VOLTAGE	4.5	Vdc
MAX OPERATING VOLTAGE	10	Vdc
CURRENT CONSUMPTION (MAX)	0.5	mA
IMPEDANCE	1.0	k0hm
SIGNAL TO NOISE RATIO (MIN.)	60	dB
TERMINAL	SOLDER PADS	-
INTERNAL CAPACITOR	N/A	pF

	REVISIONS				
LTR	DESCRIPTION	DATE	APPROVED		
1	RELEASED FROM ENGINEERING	3/23/06			
Α	ADDED TERMINAL POLARITY	2/1/07			







NOTES:

- 1. ALL DIMENSIONS ARE IN MILLIMETERS.
- 2. SPECIFICATION SUBJECT TO CHANGE OR WITHDRAWAL WITHOUT NOTICE.
- 3. THIS PART IS RoHS 2002/95/EC COMPLIANT
- 4. MICROPHONE CLOTH OVER FACE IS IP51 RATED.

FILE NAME	
BOM-6538I -R.DWG	

UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN MILLIMETERS, TOLERANCES ARE ±0.5 AND ANGLES ARE ±3.*		projects ® unlimited Dayton , Ohio					
APPROVALS DATE		MICROPHONE					
DRAWN 7G	3/06						
APPROVED BR	3/06	SIZE A	DRAWING NO.				
APPROVED EP	3/06	А	BOM-6538L-R				
DO NOT SCALE DRA	AWING	SCALE: N.T.S.			SHEET 1	OF	1