

THIS DOCUMENT CONTAINS DATA PROPRIETARY TO PROJECTS UNLIMITED, INC. ANY USE OR REPRODUCTION, IN ANY FORM, WITHOUT PRIOR WRITTEN PERMISSION OF PROJECTS UNLIMITED, INC. IS PROHIBITED.


SPECIFICATIONS

PARAMETERS	VALUES	UNITS
DIRECTIVITY	OMNI	_
SENSITIVITY	-44±3	dB
STANDARD OPERATING VOLTAGE	2.0	Vdc
MAX OPERATING VOLTAGE	10	Vdc
CURRENT CONSUMPTION (MAX)	0.5	mA
IMPEDANCE	2.2	k0hm
SIGNAL TO NOISE RATIO (MIN.)	60	dB
TERMINAL	SOLDERLESS	_
INTERNAL CAPACITOR	33	pF

	REVISIONS				
LTR	DESCRIPTION	DATE	APPROVED		
-	RELEASED FROM ENGINEERING	3/23/06			







NOTES:

- 1. ALL DIMENSIONS ARE IN MILLIMETERS.
- 2. SPECIFICATION SUBJECT TO CHANGE OR WITHDRAWAL WITHOUT NOTICE.
- 3. THIS PART IS RoHS 2002/95/EC COMPLIANT.
- 4. MICROPHONE CLOTH OVER FACE IS IP51 RATED.

FILE NAME	
POM-2744S-CSS-R.DWG	

DIMENSIONS	UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN MILLIMETERS, TOLERANGES ARE ±0.5 AND ANGLES ARE ±3".		projects ® unlimited Dayton , Ohio			
AP	PROVALS	ALS DATE ELECTRET CONDENSER MICROPHONE				
DRAWN	TG	3/06				
CHECKED	BR	3/06	SIZE DRAWING NO. A POM-2744S-C33-R			
APPROVED	EP	3/06	А		OM-2/44	2-C33-K
DO NOT SCALE DRAWING		SCAL	LE: N.T.S.		SHEET 1 OF 1	