MICRO SWITCH
FREEPORT ILLINOIS, U.S.A
A DIVISION OF HONEYWELL
FED. MFG. CODE 91929

SWITCH - BASIC

BA-3ST



CIRCUIT DIAGRAM



NOTES
1 - MOUNTING HOLES WILL ACCEPT PINS OR SCREWS OF .139 MAX. DIA ON 1.000±.002 CENTERS
2 - SUITABLE ONLY FOR APPLICATIONS IMPARTING A RAPID STROKE TO THE SWITCH PLUNGER

THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH, A DIVISION OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH.

THIRD ANGLE PROJECTION

CHARACTERISTICS

OPERATING FORCE — — — — 26-38 OZ
RELEASE FORCE — — — — — 10 OZ MIN
DIFFERENTIAL TRAVEL — — — .007-.015
OVERTRAVEL — — — — — — .010 MIN

ELECTRICAL DATA

CONTACT ARRANGEMENT
SEE CIRCUIT DIAGRAM

30 VOLTS D C RATING (SEA LEVEL TO 50,000 FT)
INDUCTIVE — — — — — — — — — — — — 25 AMP
RESISTIVE — — — — — — — — — — — — 30 AMP
MAXIMUM INRUSH — — — — — — — — — 75 AMP
BASED ON LIFE OF 25,000 OPERATIONS

25A 125, 250, OR 480 VAC L58
3/4 HP 125 VAC, 11/2 HP 250 VAC
1A 125 VDC, 0.5A 250 VDC

SCALE FULL
DO NOT SCALE PRINT

TOLERANCES
APPLY TO DESIGN UNITS. CONVERSIONS ARE ONLY FOR REFERENCE. UNLESS NOTED, TOLERANCES ARE ±

	DIM. mm	TOL. mm/in	DIM. in	TOL. mm/in
NO PLACES	X	1/.04		
ONE PLACE	X.X	0.4/.016	X.X	0.8/.03
TWO PLACES	X.XX	0.15/.006	X.XX	0.38/.015
THREE PLACES			X.XXX	0.13/.005
ANGLES				

SI METRIC ☐ US CUSTOMARY ☒
DESIGN UNITS

WEIGHT .067 LB

REVISIONS

A	CO 53551	S L B 15 SEPT 83
B	0063005	J A P 5 APR 88
C	CO-59351-0	JWB 18 JUL 91
D	205503	G J W 1 MAY 02

BA-3ST PAGE 1 OF 1
DRAWING NUMBER M
ISSUE 11
RELEASE NO.
REPLACES
CHECK
DRAWN RASTER
S L B 15 SEPT 83
FO-52848-A

Downloaded from Elcodis.com electronic components distributor