



NOTE  
1 - SWITCH MATERIALS WILL WITHSTAND 150°C

<b>CHARACTERISTICS</b> OPERATING FORCE----- 81 GRAMS MAX RELEASE FORCE----- 8 GRAMS MIN DIFFERENTIAL TRAVEL----- .028 MAX OVERTRAVEL----- .070 MIN RELEASE TRAVEL----- .017 MIN		<b>ELECTRICAL DATA</b> CONTACT ARRANGEMENT S P N O  L162 5A 125, 250, 277 VAC 1/10HP 250 VAC 		UNLESS OTHERWISE SPECIFIED TOLERANCES ARE: NO PLACE X ±.040 ±1 ONE PLACE .X ±.030 ±0.4 TWO PLACE .XX ±.015 ±0.15 THREE PLACE .XXX ±.005 ± ANGLES ± RAW MATERIAL-COMMERCIAL STANDARD		DRAWN TSM 6FEB03 CHECK SAV 6FEB03		<b>Honeywell</b>  <b>SWITCH, BASIC</b>	
		THIRD ANGLE PROJECTION 		THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE PERMISSION OF HONEYWELL.		TITLE SIZE DWG TYPE DRAWING NAME REV <b>B I V7-1A23D8-022 1</b>			
				DIMENSIONS ARE TO BE MET BEFORE PROTECTIVE COATINGS ARE APPLIED		SCALE 2 : 1 WEIGHT SHEET 1 OF 1			