



EX-Q



Actual product appearance may vary.

**Explosion-Proof Limit Switches Series
EX: Top Plunger; 1NC 1NO SPDT Snap
Action; 0.5 in - 14NPT conduit**

Features

- NEMA 1, 7, and 9
- Compact, rugged housing
- Up to 20 amp capacity
- Ample wiring space
- Mounts from four sides
- Roller arms adjustable through 360 degrees
- Non-sparking actuators
- Captive cover screws
- UL listed, file #E14274
- CSA certified, file #LR57324
- ATEX approved, file #KEMA 04ATEX2312 X
- Grounding screw

Potential Applications

- Control valves and actuators
- Petro-chemical plants
- Conveyors
- Material handling

Description

MICRO SWITCH™ EX switches feature the smallest UL-listed housings available for use in hazardous locations. Flame paths within the housing cool exploding gases below the kindling temperature before they reach the explosive gases surrounding the housing.

Product Specifications	
Availability	Global
Operating Force (O.F.)	13,34 N [3.0 lb] max.
Pretravel (P.T.)	1,98 mm max. [0.078 in max.]
Overtravel (O.T.)	4,78 mm min. [0.188 in min.]
Differential Travel (D.T.)	0,10 mm max. [0.004 in max.]
Product Type	MICRO SWITCH™ Explosion-Proof Limit Switches
Actuator	Top Plunger
Circuitry	1NC 1NO SPDT Snap Action

Ampere Rating	15 A Ind./ 0.5 A Res./0.25 A Res.
Supply Voltage	125 Vac, 250 Vac, 480 Vac/125 Vdc/250 Vdc
Housing Material	Aluminum
Termination Type	0.5 in - 14NPT conduit
Housing Type	EX
Series Name	EX
Sealing	NEMA 1, 7 (Class I, Division 1, Groups C, D), 9 (Class II, Division 1, Groups E, F, G)
Approvals	UL listed, CSA Certified, ATEX approved
CSA File #	LR57324
UL File #	E14274
ATEX File #	KEMA 04ATEX2312 X
Operating Temperature Range	-40 °C to 71 °C [-40 °F to 160 °F]
UNSPSC Code	302119
UNSPSC Commodity	302119 Switches and controls and relays
Sealed	Explosion-proof
Operating Position (O.P.)	52,32 mm [2.060 in]

