

E-mail: saleshelp@tripplite.com



# Model #: BP36V27

#### BP36V27 - External Battery Pack for UPS System



## **Highlights**

- Extends runtime of select compatible Tripp Lite UPS Systems with 36V DC external battery connector
- Provides daisy-chain capability
- · Simple installation; tower and stack adaptable
- 2 year warranty

### **Description**

BP36V27 tower external battery pack offers extended battery runtime when used in conjunction with Tripp Lite SMART750XL, SMART1050XL & SMART1500XL UPS systems supporting a 36V external battery connection. Includes heavy gauge cabling with high current DC connectors for simple installation. Additional output connector allows multiple BP36V27 battery packs to be daisy-chained to the UPS for even longer extended run operation.

COMPATIBLE UPS SYSTEMS: SMART750XL, SMART1050XL, SMART1500XL, SMARTINT1400XL and other Tripp Lite UPS systems that specify the use of this battery pack.

#### Applications

• Ideal means of lengthening the battery runtime provided by compatible Tripp Lite UPS systems. Additional battery packs may be ordered at time of original UPS purchase or sourced at a later date to extend runtime performance if site power conditions deteriorate and longer battery runtime is desired.

# Package Includes

- BP36V27 external battery pack
- Warranty information
- Instruction manual

## **Features**

- Offers extended-run UPS operation when used in conjunction with compatible Tripp Lite UPS systems
- Set of two input/output connectors allows multiple BP36V27 battery packs to be daisy-chained to the UPS for even longer extended run operation
- Pre-wired internal battery sets are ready for installation with no user battery connections required
- Includes heavy gauge cabling with high current DC connectors for simple installation
- Matches cabinet appearance of the companion UPS
- 2 year warranty

### **Specifications**

BATTERY	
Expandable battery runtime	Gray 50 amp female DC connector for additional battery packs
DC system voltage (VDC)	36
Connects to UPS via	Attached cable with grey 50 amp DC connector
Typical battery lifespan	4-6 years typical (North America)
PHYSICAL	
Shipping weight (lbs)	62
Unit Dimensions (HWD/in)	7 x 8.5 x 14.5
Unit Dimensions (HWD/cm)	17.8 x 21.6 x 36.9
Unit weight (lbs)	56.4
Material of construction	Black polycarbonate
Form factors supported	Floorstanding tower format, stackable - supports wallmount with optional UPSWM accessory
CERTIFICATIONS	
Certifications	Tested to UL, cUL, CE, NOM
WARRANTY	
Product Warranty Period (U.S., Canada & Puerto Rico)	2-year limited warranty
Optional Coverage	3 year, 5 year, next day and on-site warranty coverage available

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?txtModelID=2498.

Copyright © 2011 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.