BP36V142U External Battery Pack for UPS Systems



Model #: BP36V14-2U

- Extends runtime of select compatible Tripp Lite UPS Systems with 36VDC external battery connector
- Provides daisy-chain capability
- Simple installation; 2U rackmount, tower and stack adaptable
- 2 year warranty

DESCRIPTION

BP36V142U rack/tower external battery pack offers extended battery runtime when used in conjunction with compatible Tripp Lite systems. Multi-use form factor supports configuration in stacking, upright tower and rackmount applications using only 2 rack spaces (2U). Includes heavy gauge cabling with high current DC connector for simple installation. Additional output connector allows multiple BP36V142U battery packs to be daisy-chained to the UPS for even longer extended run operation.

Compatible UPS Systems: SU1000RTXL2U, SUINT1000RTXL2U and other Tripp Lite UPS systems that specify the use of this battery pack.

KEY BUYING POINTS

- Offers extended-run UPS operation when used in conjunction with compatible Tripp Lite UPS systems
- Supports stacking or rackmount installation using only 2 rack spaces (2U)
- Includes heavy gauge cabling with high current DC connectors for simple installation
- Ships in gray color, user installable black front bezel enables coordination with black equipment racks
- Additional output connector allows multiple BP36V142U battery packs to be daisy-chained to the UPS for even longer extended run
 operation
- 2 year warranty

TYPICAL APPLICATIONS

Ideal means of lengthening the battery runtime provided by compatible Tripp Lite UPS systems. Battery pack may be ordered at time
of original UPS purchase or sourced at a later date to extend runtime performance if site power conditions deteriorate and longer
battery runtime is desired.

OPTIONS & ACCESSORIES

- Extended warranties: 3 Year <u>WEXT3-BP36V</u>, 5 Year <u>WEXT5-BP36V</u>
- Two-post rackmount/wallmount kit: <u>2POSTRMKITWM</u>
- Tower stands: <u>2-9USTAND</u>

PACKAGE INCLUDES

- BP36V142U external battery pack
- Mounting hardware
- Warranty information
- Instruction manual

COMPLETE SPECIFICATIONS

BATTERY

Expandable battery runtime:	JPS specific female connector for additional battery packs
DC system voltage: 3	36V DC
Typical battery lifespan: 4	I-6 years typical (North America)
Connects to UPS via: 1	ft. detachable cable with UPS specific DC connector
PHYSICAL	
Shipping weight (lbs): 5	54
Unit weight (Ibs): 4	14
Unit Dimensions (HWD/in): 3	3.5 x 17.25 x 12.75
Material of construction: B	Black steel cabinet
Form factors supported: 2	2U rackmount housing
CERTIFICATIONS	
Certifications:	JL, cUL, CE, NOM
WARRANTY	
Optional coverage: 3	3 year, 5 year, next day and on-site warranty coverage available
Product warranty: 2	2 year product warranty

The policy of Tripp Lite is one of continuous improvement. Specifications are subject to change without notice. Therefore, your product may vary slightly from what is currently listed.



Tripp Lite World Headquarters 1111 W. 35th Street Chicago, IL 60609 USA

> Customer Support (773) 869-1234

© 2006 Tripp Lite. All Rights Reserved.