

This document was generated on 05/19/2011

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: Status:	<u>0473590001</u> Active		
Overview: battery connectors Description: 2.00mm (.079") Pitch Battery (Height 2.10mm (.083"), 4 Circle		Connector, SMT, Contact Width 7.00mm (.276"), Working cuits, Lead-free	
Documents:			
<u>3D Model</u> Drawing (PDF)		Product Specification PS-47359-001 (PDF) RoHS Certificate of Compliance (PDF)	Serie
Product Family		PCB Headers	
Series		47359	EU RoHS China RoHS
Application		Board-to-Board, Signal	ELV and RoHS
Overview		battery_connectors	Compliant
Product Name		Battery Connector, Compression Connector, One Piece	REACH SVHC
			Contains SVHC: No
Physical			Low-Halogen Status
Breakaway		No	Low-Halogen
Circuits (Loaded)		4	Need more information on product
Circuits (maximum)		4	environmental compliance?
Durability (mating cycles max)		10,000	environmental compliance :
First Mate / Last Break		No	Email productcompliance@molex.com
Glow-Wire Compliant		No	For a multiple part number RoHS Certificate
Guide to Mating Part		No	Compliance, <u>click here</u>
Keying to Mating Part		None	• • •
Lock to Mating Part		None	Please visit the Contact Us section for any
Material - Plating Mating		Gold	non-product compliance questions.
Material - Plating Termination		Tin	
Material - Resin		High Temperature Thermoplastic	
Number of Rows		1	
Orientation		Vertical	Search Parts in this Series
PCB Locator		No	47359Series
PCB Retention		None]
Packaging Type		Embossed Tape on Reel	
Pitch - Mating Interface		2.00mm (.079")	
Pitch - Termination Interface		2.00mm (.079")	
Plating min - Mating		0.762µm (30µ")	
Plating min - Termination		3.810µm (150µ")	
Polarized to Mating Part		No	
Polarized to PCB		No	
Shrouded		No	
Stackable		No	
Surface Mount Compatible (SMC)		Yes	
Temperature Range	1 0	-40°C to +85°C	
Termination Interfac	e: Style	Surface Mount	
Electrical			
Current - Maximum per Contact		1A	
Voltage - Maximum		200V (RMS)	
Solder Process	Data		
Duration at Max. Process Temperature (seconds)		30	
Lead-free Process Capability		Reflow Capable (SMT only)	
Max. Cycles at Max. Process Temperature		2	
Process Temperature max. C		250	

Material Info

Reference - Drawing Numbers Product Specification Sales Drawing

PS-47359-001 SD-47359-001

This document was generated on 05/19/2011 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION