

4



3

2

1

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION  
 © COPYRIGHT - BY TYCO ELECTRONICS CORPORATION. ALL RIGHTS RESERVED.

LOC	DIST	REVISIONS			
P	LTR	DESCRIPTION	DATE	DWN	APVD
AD	00				
	C1	REVISED PER ECO-05-013282	12/18/07	SS	MS



**Materials:**  
 BASE/COVER-PCT UL94V-0, BLACK  
 ACTUATOR-NYLON PA46 UL94V-0, NATURAL  
 MOVING CONTACT-COPPER ALLOY, SILVER OVER NICKEL  
 FIXED CONTACT-COPPER ALLOY, SILVER OVER NICKEL  
 TERMINAL-COPPER ALLOY, TIN/LEAD OVER NICKEL OR TIN OVER NICKEL




**Electrical:**  
 Contact Rating, 300 milliamp @ 115V AC Per EIA-448, Method 6  
 Contact resistance, 40 milliohms max @ 100mA 2-4V DC, Per EIA-364-23B, each position  
 Insulation Resistance, 1000 Megohm Min @ 500V DC, Per EIA-364-21C each position  
 Dielectric strength, 600 V RMS@ Sea level, Per EIA-364-20B, Condition 1, each position  
 Life Expectancy, Electrical, 15,000 cycles @ full load

**Mechanical:**  
 Actuation force, 800 grams max  
 Actuation Travel, .100 +/- .010  
 Life Expectancy, 15,000 cycles

**Environmental:**  
 Operating Temperature, -40 to +80 degrees C, Per EIA 448, Method 10  
 Storage Temperature, -40 to +80 degrees C  
 Humidity and Temperature Cycling Per EIA-364-31B, Method III  
 Solderability, Per EIA-364-52, Class 2, Category 1, 95% Minimum coverage  
 Resistance to Solder Heat, Per 109-202, Condition B  
 Process cleaning-will withstand aqueous or solvent cleaning processes

**NOTES:**  
 1. PARTS TO BE PACKAGED IN 22 INCH TUBES.

⚠ ALL MATERIALS AND FINISHES SHALL COMPLY WITH EU DIRECTIVE 2002/95/EC OF 27JAN2003 (ROHS)



P.C.B. LAYOUT

⚠	ASE7125604	1825468-1
-	ASE71256	5-1437581-4
NOTES	T&B NUMBER	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN M. BINNER 02AUG04	Tyco Electronics Corporation Harrisburg, Pa 17105-3608	
DIMENSIONS: INCHES		CHK M. SARVER 02AUG04	NAME SPECIAL ASE PC MOUNTING	
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD M. SARVER 02AUG04	RESTRICTED TO	
0 PLC ± -		PRODUCT SPEC	-	
1 PLC ± -		APPLICATION SPEC	-	
2 PLC ± -		WEIGHT	-	
3 PLC ± .010		SIZE	A3	
4 PLC ± -		CAGE CODE	00779	
ANGLES ± 1°		DRAWING NO	5-1437581-4	
MATERIAL	FINISH	SCALE	2:1	
-	-	CUSTOMER DRAWING	SHEET 1 OF 1 REV C1	