## **GROUND**

## 35 and 32mm DIN Rail

Use ground blocks instead of grounding studs and wire lugs to terminate ground wires, saving installation and wiring time.

Ground blocks clamp mechanically onto the DIN Rail by tightening the center mounting screw, making a reliable electrical connection between the cage clamp terminals and the DIN Rail. The rail serves as a busbar and automatically distributes ground potential to all other ground terminals on the same rail.

Ground blocks can also be used as end stops, preventing other terminal blocks and components from moving laterally on the DIN Rail.

They are supplied with a standard green/yellow housing for easy identification and accept standard marking tags.

CGT4U, CGT10U and CGT35U can be mounted on both DIN 32mm and DIN 35mm rails.

CGT4N & CGT6N can be mounted on 35mm DIN rail and have the same top outer profile as the feed through blocks (CTS4U-N, CTS2.5U-N, CTS6U, CTS10U).

CGMT4 can be mounted on 15mm DIN rails and has the same top outer profile as the CMT4 feed through blocks.

- · High density
- Screw-cage clamp
- Special clamping foot
- Polyamide 6.6
- · Color: green/yellow



Terminal Width

Height x Length

Stripping Length

Insulation Material

Type of Connection


**Approvals** 

Wire Range

Marking Tags

(MTType)

Torque



AEx eII EEx eII
mm

CGT4U



CGT4N

Type taxted
6 mm
48 x 43 mm
9 mm
Polyamide 6.6

45.4 x 54.2 mm	
9 mm	
Polyamide 6.6	
2 screw clamps	

6 mm

7 lb-in

	2 001011 01		
	$_{\rm C}$ $_{\rm US}$	<b>VDE</b>	C US E220514
	22-10 AWG	0.5-4 sq.mm	22-10 AWG
	7 lb-in	0.5 Nm	7 lb-in

2 screw clamps



0.8 Nm

7 lb-in

Std. Pk.

Terminal Block	
DIN Rail for ordering information refer to page 62	n
End Plate	

Cat. No.	Std. Pk.	Cat. No.
CGT4N	50	CGT4N
EPCGT4U	100	EPCGT4
MT6	100	MT6

Otta. i K.
50
100
100



