

MSPF101C

TE Part Number: 9-1437567-3





Product Highlights:

- · Switch Mechanical
- Not Tactile
- Single Pole Single Throw Configuration (Pole-Throw)

Always EU RoHS/ELV Compliant (Statement of Compliance)

- Contact Rating = 0.5A
- Operating Function = Normally Open, Momentary

View all Features | Find Similar Products

• Check
Pricing &
Availability

AvailabilitySearch for Tooling

• Product
Feature
Selector

• Contact Us

About This

Product

Documentation & Additional Information

Product Drawings:

• PUSH BUTTON MOMENTARY (MSPF-101B AND C SERIES) (PDF, English)

Catalog Pages/Data Sheets:

• ALCOSWITCH PRODUCTS (PDF, English)

Product Specifications:

• None Available

Application Specifications:

None Available

Instruction Sheets:

None Available

CAD Files:

• None Available

Additional Information:

• Product Line Information

Related Products:

• <u>Tooling</u>

List all Documents

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- Product Type = Switch Mechanical
- Tactile = No
- $\bullet \quad Configuration \ (Pole-Throw) = Single \ Pole \ \ Single \ Throw$
- Mount Angle = Vertical
- $\bullet \ \ Termination \ Type = Wire \ Lugs$
- Actuator Style = Round
- Comment = Versatile front or rear entry, with hardware supplied.

Electrical Characteristics:

• Contact Rating = 0.5A

Body Related Features:

- $\underline{Series} = MSPF$
- Mount Style = Panel
- Actuator Length (mm [in]) = 6.50 [0.256]
- Actuator Profile = Extended
- Actuator Color = Red
- Bushing Diameter = 15/32
- Case Material = Thermoset
- Actuator Material = Thermoplastic

Contact Related Features:

• Contact Plating = Silver

Housing Related Features:

- Process Sealed = No
- Low Profile = No
- Bushing Style = Threaded

Configuration Related Features:

- Operating Function = Normally Open, Momentary
- Ganged = No
- ESD Grounding Terminal = Without
- Number of Actuators = Single
- Illuminated = No
- Dust Proof = No
- Support Bracket = Without
- Snap Action = Without

Industry Standards:

- RoHS/ELV Compliance = RoHS compliant, ELV compliant
- <u>Lead Free Solder Processes</u> = Hand solderable with lead free solder
- RoHS/ELV Compliance History = Always was RoHS compliant

Conditions for Usage:

• Temperature Rating = Standard

Packaging Related Features:

• Packaging Method = Loose Piece

Other:

• Brand = Alcoswitch