

## NTE5340, NTE5342 & NTE5344 Silicon Bridge Rectifier Single-Phase, 40 Amp

**Electrical Characteristics Per Leg:** ( $T_A = +25^\circ\text{C}$ , unless otherwise specified)

Peak Reverse Voltage,  $P_{RV}$

NTE5340 .....	200V
NTE5342 .....	600V
NTE5344 .....	1000V

Average Forward Current ( $T_C = +55^\circ\text{C}$ ),  $I_F (\text{AV})$  ..... 40A

Maximum Peak Surge Current (8.3ms),  $I_{FSM}$  ..... 300A

Maximum Instantaneous Forward Voltage Drop ( $I_F = 20\text{A}$ , Note 1),  $V_F$  ..... 1.2V

Maximum DC Reverse Current @  $P_{RV}$ ,  $I_R$

$T_A = +25^\circ\text{C}$ .....	10 $\mu\text{A}$
$T_A = +100^\circ\text{C}$ .....	100 $\mu\text{A}$

Thermal Resistance, Junction-to-Case (Total Bridge),  $R_{thJC}$  ..... 1.2 $^\circ\text{C}/\text{W}$

Maximum Operating Temperature,  $T_{opr}$  ..... +175 $^\circ\text{C}$

Storage Temperature Range,  $T_{stg}$  ..... -55 $^\circ$  to +175 $^\circ\text{C}$

Note 1. Pulse Width < 300 $\mu\text{s}$ , Duty Cycle < 2.0%

