












European and Universal Jumper Cords










**RoHS
Compliant**

QUALTEK ELECTRONICS

Continental Europe




Part Number	Figure	Length Meters	Cordage	# Cond mm ²	Amp Rating	Plug No.	Conn No.	PDF Drawings
360006-E01	A	2 M	H03VVH2-F	2 x 0.75	2.5 A	IEC 884/EN 50 075	IEC 60320 C7	
361014-D01	B	2.5 M	H03VVH2-F	2 x 0.75	2.5 A	CEE 7/XVI	--	
361016-D01	B	2.5 M	H05VVH2-F	2 x 0.75	2.5 A	CEE 7/XVI	--	
361020-D01	B	2.5 M	H03VV-F	2 x 0.75	2.5 A	CEE 7/XVI	--	
361022-D01	B	2.5 M	H05VV-F	2 x 0.75	2.5 A	CEE 7/XVI	--	
362001-E01	C	2.5 M	H03VVH2-F	2 x 0.75	6 A	Continental Europe	--	
362002-E01	C	2.5 M	H05VVH2-F	2 x 0.75	6 A	Continental Europe	--	
362003-E01	C	2.5 M	H03VV-F	2 x 0.75	6 A	Continental Europe	--	
362004-E01	C	2.5 M	H05VV-F	2 x 0.75	6 A	Continental Europe	--	
362005-E01	C	2.5 M	H05VV-F	2 x 1.00	10 A	Continental Europe	--	



363010-D01	D	2.5 M	H05VV-F	3 x 0.75	6 A	Continental Europe CEE 7/7	--	
363012-D01	D	2.5 M	H05VV-F	3 x 1.00	10 A	Continental Europe CEE 7/7	--	
363014-D01	D	2.5 M	H05VV-F	3 x 1.50	15 A	Continental Europe CEE 7/7	--	
364002-D01	E	2.5 M	H05VV-F	3 x 1.00	10 A	IEC 884/CEE 7/VII	IEC 60320 C13	
366040-D01	F	2.5 M	H05VV-F	3 x 0.75	6 A	IEC 884/CEE 7/VII	--	
366042-D01	F	2.5 M	H05VV-F	3 x 1.00	10 A	IEC 884/CEE 7/VII	--	
366044-D01	F	2.5 M	H05VV-F	3 x 1.50	16 A	IEC 884/CEE 7/VII	--	
367003-D01	G	2.5 M	H05VV-F	3 x 1.00	10 A	IEC 884/CEE 7/VII	IEC 60320 C13	
387001-E01	H	1.0 M	H05VV-F	3 x 0.75	6 A	IEC 60320 C14	IEC 60320 C13	
387002-E01	H	1.0 M	H05VV-F	3 x 1.00	10 A	IEC 60320 C14	IEC 60320 C13	

QUALTEK ELECTRONICS


Universal Jumper Cords



I

Part Number	Figure	Length Meters	Cordage	# Cond mm ²	Amp Rating	Plug No.	Conn No.	PDF Drawings
319002-T01	I	1.0 M	H05VV-F/SJT	3 x 1.00	10 A	IEC 60320 C14	IEC 60320 C13	
319004-T01	I	2.5 M	H05VV-F/SJT	3 x 1.00	10 A	IEC 60320 C14	IEC 60320 C13	

REVISION			
REV.	DESCRIPTION	DATE	APPROVED
B	RoHS Compliancy	06-01-06	DP
C	Updated Specifications	01-10-08	DP
D	Updated Approvals	01-25-08	DP



CONTROLLED

NOTES:

1. CORDAGE: H05VV-F/SJT, 18AWG / 3C, 3x1.00mm²
CEE COLOR CODE, TEMP. RATING 105°C,
RATING: 250V 10A, JACKET COLOR: BLACK
2. PLUG: IEC 60320 C14
3. CONNECTOR: IEC 60320 C13
4. APPROVALS: UL, cUL, VDE, CB, CEBC, DEMKO, FIMKO,
IMQ, KEMA, NEMKO, OVE, SAA, SEMKO, SEV
5. HANK AND TIE
6. ROHS COMPLIANT

Dim range (mm)	Tolerance +/- (mm)	Qualtek Electronics Corp. PPC DIVISION		
		Part Number: 319004-T01	RoHS Compliant	
0-1	0.15	Description: POWER CORD		
1-6	0.20			
6-18	0.30		UNIT: in	REV. D
18-50	0.50			
50-120	0.70	Drawn / Date	Checked / Date	Approved / Date
120-250	0.90	B.Zhang 10-28-00	10-28-00	JJH / 10-28-00
250-500	1.20			