

## Model #: 6SP

## Waber-by-Tripp Lite Power Strip - Multiple outlet strip with relocatable power tap



#### **Highlights**

6 outlets

6-ft. cord

13.7-in. overall length

Lighted master power switch

## **Description**

The Waber-by-

Includes 6 NEMA 5□

in a wide variety

single AC wall

rugged all-metal h□

blue/gray color scheme. Lifetime warranty.

PLUG/OUTLETS - Input: NEMA 5-15P/Output: 6 NEMA 5-15R

ELECTRICAL - 120V AC, 50/60Hz, 15A (Requires standard NEMA 5-15R wall receptacle)

FORMAT - Corded power distribution strip

#### Applications

Offers multiple

ideal for distributing alternate waveform UPS or generator power to protected equipment.

## Package Includes

6SP Power Strip

Warranty information

Instruction manual

#### **Features**

Multi-outlet power strip offers convenient power distribution in workbench, wallmount or floor mount applications Includes 6 NEMA 5-15R output receptacles with 1.625-in. center-to-center outlet spacing Lighted power switch with transparent snap-over guard to prevent accidental shutoff Keyhole mounting tabs support permanent installation on a wide variety of surfaces

UL1363 (USA), cUL (Canada)

15A power handling capacity with circuit breaker

6-foot AC line cord

# **Specifications**

Votage compatibility         120VAC           Frequency compatibility         50/60 Hz           OUTPUT           Output voit amp capacity (amps)         15A           Outlet quantity / type         6 NEMA 5-15R           Outlet orientation         Single row of 6           Outlet spacing         1.625 in.           INPUT         Input cornection type           Input cord length (ft.)         6           Input cord length (m)         1.8288           Recommended Electrical Service         15A 120V           Service         Illuminated 2-position switch controls power to all outlets           LebS ALARMS & SWITCHES         Illuminated 2-position switch cover prevents accidental shutoff           PHYSICAL           Unit Dimensions (HWD/in)         12.5 x 2.5 x 1.5           Unit Dimensions (HWD/in)         31.75 x 6.35 x 3.8           Material of construction         Metal           Integrated keyhole mounting tabs enable mounting to a variety of surfaces table for cord color         Black           & C line cord color         Black           & C line cord color         Black           WLI 2363 (Power Tap)         UL 1363           UL/ CSA (Canada)         UL           WARRANTY         Very County of the counting table for counting	SYSTEM OVERVIEW	
OUTPUT Output volt amp capacity (amps) Outlet quantity / type 6 NEMA 5-15R Outlet orientation Single row of 6 Outlet spacing 1.626 in.  INPUT Input connection type NEMA 5-15P Input cord length (ft.) 6 Input cord length (m) 1.8288 Recommended Electrical Service Illuminated 2-positon switch controls power to all outlets Locking switch cover Transparent locking switch cover prevents accidental shutoff PHYSICAL Unit Dimensions (HWD/in) 12.5 x 2.5 x 1.5 Unit Dimensions (HWD/cm) Metal Integrated keyhole mounting tabs enable mounting to a variety of surfaces tabs Receptacle Color Black CERTIFICATIONS UL1363 (Power Tap) UL1363 CUL / CSA (Canada)  WARRANTY	Voltage compatibility	120VAC
Output voit amp capacity (amps)  Outlet quantity / type 6 NEMA 5-15R  Outlet quantity / type 6 NEMA 5-15R  Outlet spacing 1.625 in.  INPUT  Input connection type NEMA 5-15P  Input cord length (ft.) 6  Input cord length (fm) 1.8288  Recommended Electrical Service 15A 120V  Service Illiuminated 2-position switch controls power to all outlets  Locking switch cover Transparent locking switch cover prevents accidental shutoff  PHYSICAL  Unit Dimensions (HWD/In) 12.5 x 2.5 x 1.5  Unit Dimensions (HWD/Icm) Metal  Integrated keyhole mounting tabs enable mounting to a variety of surfaces tabs  Recoptacle Color Black  AC line cord color Black  CERTIFICATIONS  UL 1363 (Power Tap) UL 1363  CUL / CSA (Canada) v. ACR	Frequency compatibility	50/60 Hz
Outlet quantity / type 6 NEMA 5-15R Outlet orientation Single row of 6 Outlet spacing 1.625 in. INPUT Input connection type NEMA 5-15P Input cord length (ft.) 6 Input cord length (ft.) 6 Input cord length (ft.) 1.8288 Recommended Electrical Services Illuminated 2-position switch controls power to all outlets LOCKING Switch cover Transparent locking switch cover prevents accidental shutoff PHYSICAL Unit Dimensions (HWD/in) 1.2.5 x 2.5 x 1.5 Unit Dimensions (HWD/cm) 31.75 x 6.35 x 3.8 Material of construction Metal Integrated keyhole mounting tabs enable mounting to a variety of surfaces table and color Black AC line cord color Black AC line cord color Black CERTIFICATIONS UL1363 (Power Tap) UL1363 CUL / CSA (Canada) CUL WARRANTY	OUTPUT	
Outlet orientation Single row of 6 Outlet spacing 1.625 in.  INPUT Input connection type NEMA 5-15P Input cord length (ft.) 6 Input cord length (m) 1.8288 Recommended Electrical Service 15A 120V Service Illuminated 2-positon switch controls power to all outlets LEDS ALARMS & SWITCHES Switches Illuminated 2-positon switch cortrols power to all outlets Locking switch cover Transparent locking switch cover prevents accidental shutoff PHYSICAL Unit Dimensions (HWD/in) 12.5 × 2.5 × 1.5 Unit Dimensions (HWD/cm) 31.75 × 6.35 × 3.8 Material of construction Metal Integrated keyhole mounting tabs enable mounting to a variety of surfaces tabs  Receptacle Color Black AC line cord color Black CERTIFICATIONS UL 1363 (Power Tap) UL1363 cUL / CSA (Canada) CUL WARRANTY		15A
New Part of the spacing of the spaci	Outlet quantity / type	6 NEMA 5-15R
INPUT  Input connection type NEMA 5-15P  Input cord length (ft.) 6  Input cord length (m) 1.8288  Recommended Electrical Service 15A 120V  LEDS ALARMS & SWITCHES  Switches Illuminated 2-position switch controls power to all outlets  Locking switch cover Transparent locking switch cover prevents accidental shutoff  PHYSICAL  Unit Dimensions (HWD/im) 12.5 x 2.5 x 1.5  Unit Dimensions (HWD/cm) 31.75 x 6.35 x 3.8  Material of construction Metal  Integrated keyhole mounting tabs enable mounting to a variety of surfaces tabs  Receptacle Color Black  CERTIFICATIONS  UL 1363 (Power Tap) UL 1363  cUL / CSA (Canada) UL  WARRANTY	Outlet orientation	Single row of 6
Input connection type   NEMA 5-15P   Input cord length (ft.)   6   Input cord length (m)   1.8288   Recommended Electrical service   15A 120V   IEDS ALARMS & SWITCHES Switches   Illuminated 2-position switch controls power to all outlets   Locking switch cover   Transparent locking switch cover prevents accidental shutoff   PHYSICAL   Unit Dimensions (HWD/in)   12.5 x 2.5 x 1.5   Unit Dimensions (HWD/cm)   31.75 x 6.35 x 3.8   Material of construction   Metal   Integrated keyhole mounting   Keyhole mounting tabs enable mounting to a variety of surfaces   Integrated Color   Black   AC line cord color   Black   CERTIFICATIONS   UL1363 (Power Tap)   UL1363   CUL / CSA (Canada)   CUL   WARRANTY	Outlet spacing	1.625 in.
Input cord length (ft.) 6 Input cord length (m) 1.8288  Recommended Electrical 55A 120V  LEDS ALARMS & SWITCHES  Switches Illuminated 2-position switch controls power to all outlets  Locking switch cover Transparent locking switch cover prevents accidental shutoff  PHYSICAL  Unit Dimensions (HWD/in) 12.5 x 2.5 x 1.5  Unit Dimensions (HWD/cm) 31.75 x 6.35 x 3.8  Material of construction Metal  Integrated keyhole mounting tabs enable mounting to a variety of surfaces  Receptacle Color Black  AC line cord color Black  CERTIFICATIONS  UL1363 (Power Tap) UL1363  CUL / CSA (Canada) CUL  WARRANTY	INPUT	
Input cord length (m)  Recommended Electrical service 15A 120V  LEDS ALARMS & SWITCHES  Switches Illuminated 2-position switch controls power to all outlets  Locking switch cover Transparent locking switch cover prevents accidental shutoff  PHYSICAL  Unit Dimensions (HWD/in) 12.5 x 2.5 x 1.5  Unit Dimensions (HWD/cm) 31.75 x 6.35 x 3.8  Material of construction Metal  Integrated keyhole mounting tabs enable mounting to a variety of surfaces  Receptacle Color Black  AC line cord color Black  CERTIFICATIONS  UL1363 (Power Tap) UL1363  cUL / CSA (Canada) UL  WARRANTY	Input connection type	NEMA 5-15P
Recommended Electrical Service 15A 120V  LEDS ALARMS & SWITCHES Switches Illuminated 2-positon switch controls power to all outlets  Locking switch cover Transparent locking switch cover prevents accidental shutoff  PHYSICAL Unit Dimensions (HWD/in) 12.5 x 2.5 x 1.5  Unit Dimensions (HWD/cm) 31.75 x 6.35 x 3.8  Material of construction Metal  Integrated keyhole mounting tabs enable mounting to a variety of surfaces tabs  Receptacle Color Black  AC line cord color Black  CERTIFICATIONS  UL1363 (Power Tap) UL1363  cUL / CSA (Canada) cUL  WARRANTY	Input cord length (ft.)	6
Service  LEDS ALARMS & SWITCHES  Switches Illuminated 2-positon switch controls power to all outlets  Locking switch cover Transparent locking switch cover prevents accidental shutoff  PHYSICAL  Unit Dimensions (HWD/in) 12.5 x 2.5 x 1.5  Unit Dimensions (HWD/cm) 31.75 x 6.35 x 3.8  Material of construction Metal  Integrated keyhole mounting tabs enable mounting to a variety of surfaces tabs  Receptacle Color Black  AC line cord color Black  CERTIFICATIONS  UL1363 (Power Tap) UL1363  cUL / CSA (Canada) UL  WARRANTY	Input cord length (m)	1.8288
Switches Illuminated 2-positon switch controls power to all outlets  Locking switch cover Transparent locking switch cover prevents accidental shutoff  PHYSICAL  Unit Dimensions (HWD/in) 12.5 x 2.5 x 1.5  Unit Dimensions (HWD/cm) 31.75 x 6.35 x 3.8  Material of construction Metal  Integrated keyhole mounting Keyhole mounting tabs enable mounting to a variety of surfaces  Receptacle Color Black  AC line cord color Black  CERTIFICATIONS  UL1363 (Power Tap) UL1363  cUL / CSA (Canada) CUL  WARRANTY		15A 120V
Locking switch cover Transparent locking switch cover prevents accidental shutoff  PHYSICAL  Unit Dimensions (HWD/in)	LEDS ALARMS & SWITCHES	
PHYSICAL Unit Dimensions (HWD/in) 12.5 x 2.5 x 1.5 Unit Dimensions (HWD/cm) 31.75 x 6.35 x 3.8  Material of construction Metal Integrated keyhole mounting tabs enable mounting to a variety of surfaces tabs  Receptacle Color Black AC line cord color Black  CERTIFICATIONS UL1363 (Power Tap) UL1363  CUL / CSA (Canada) CUL  WARRANTY	Switches	Illuminated 2-positon switch controls power to all outlets
Unit Dimensions (HWD/in) 12.5 x 2.5 x 1.5  Unit Dimensions (HWD/cm) 31.75 x 6.35 x 3.8  Material of construction Metal  Integrated keyhole mounting tabs enable mounting to a variety of surfaces  Receptacle Color Black  AC line cord color Black  CERTIFICATIONS  UL1363 (Power Tap) UL1363  CUL / CSA (Canada) CUL	Locking switch cover	Transparent locking switch cover prevents accidental shutoff
Unit Dimensions (HWD/cm) 31.75 x 6.35 x 3.8  Material of construction Metal  Integrated keyhole mounting tabs enable mounting to a variety of surfaces  Receptacle Color Black  AC line cord color Black  CERTIFICATIONS  UL1363 (Power Tap) UL1363  cUL / CSA (Canada) cUL	PHYSICAL	
Material of construction     Metal       Integrated keyhole mounting tabs     Keyhole mounting tabs enable mounting to a variety of surfaces       Receptacle Color     Black       AC line cord color     Black       CERTIFICATIONS       UL1363 (Power Tap)     UL1363       cUL / CSA (Canada)     cUL       WARRANTY	Unit Dimensions (HWD/in)	12.5 x 2.5 x 1.5
Integrated keyhole mounting tabs enable mounting to a variety of surfaces  Receptacle Color Black  AC line cord color Black  CERTIFICATIONS  UL1363 (Power Tap) UL1363  CUL / CSA (Canada) CUL  WARRANTY	Unit Dimensions (HWD/cm)	31.75 x 6.35 x 3.8
Receptacle Color Black  AC line cord color Black  CERTIFICATIONS  UL1363 (Power Tap) UL1363  CUL / CSA (Canada) CUL  WARRANTY	Material of construction	Metal
AC line cord color Black  CERTIFICATIONS  UL1363 (Power Tap) UL1363  CUL / CSA (Canada) CUL  WARRANTY		Keyhole mounting tabs enable mounting to a variety of surfaces
CERTIFICATIONS  UL1363 (Power Tap) UL1363  CUL / CSA (Canada) CUL  WARRANTY	Receptacle Color	Black
UL1363 (Power Tap)         UL1363           cUL / CSA (Canada)         cUL           WARRANTY         CUL	AC line cord color	Black
CUL / CSA (Canada) CUL WARRANTY	CERTIFICATIONS	
WARRANTY	UL1363 (Power Tap)	UL1363
	cUL / CSA (Canada)	cUL
Product warranty Lifetime	WARRANTY	
	Product warranty	Lifetime