Cinch Connectors :: D-subminiature



Products :: D-subminiature

Solder Cup Socket - Basic D Series - Metal Shell

Additional Info **Contact Arrangements** Part Number Listing **Shells and Mounts**

+ MORE + MORE + MORE + MORE





Features:

Solder cup style for wire termination.

- Offered with .120 mounting holes, 4-40 clinch nuts.
- Offered in 9, 15, 25, 37, and 50 position plugs and sockets.
- Available with gold flash.
- RoHS version available
- Approvals:
 - UL Recognized Files E170218 (UL1977) and E130965 (UL1863).
 - CSA Approved File LR31996.

Insulator Material: Glass-filled polyester (white), UL 94V-O rated

Connector Shell: Steel with zinc plating and yellow chromate finish or tin plating (grounding indents on plug)

4-40 Clinch Nut: Steel with cadmium plating and yellow chromate finish.

Mechanical:

http://www.cinch.com/view_sub_product_line.cinch?section_id=24&sub_section_id=114§ion_title=D-subminiature (1 of 2) [10/1/07 3:53:23 PM]

Cinch Connectors :: D-subminiature

Individual Contact Insertion and Separation Force (minimum/maximum): 0.7 oz./12 oz.

Durability: 500 mating cycles

Electrical:

Withstanding Voltage: Minimum 1250V RMS @ sea level

Current Rating: 5 Amps

Contact Resistance: 2.7 milliohms maximum

Insulation Resistance: 5000 megohms maximum (initial); 1000 megohms (minimum) after environmental testing

Environmental: Operating Temperature: -65°C to + 125°C

Shock: 50G peak per MIL-STD-202, Method 213, Condition G
Vibration: 12 cycles in three perpendicular directions @ 10-2000Hz, per MIL-STD-202, Method 204, Condition D

Moisture Resistance: 90-95% relative humidity @ 40°C for 96 hours per MIL-STD-202, Method 103

Back to Top

Click here for more information on this product.

© 2007 Cinch Connectors

All Rights Reserved

http://www.cinch.com/view_sub_product_line.cinch?section_id=24&sub_section_id=114§ion_title=D-subminiature (2 of 2) [10/1/07 3:53:23 PM]