

Switching element for Keylock- and Selector switch 3 positions

including Locking pin



	Contacts	Typ-Nr.	Component layout		
			Component layout	Circuit drawing	
Switching element for Keylock- and Selector switch 3 positions	2 NC + 2 NO	71-672.026	1	6	0.005

Contacts: NC = Normally closed, NO = Normally open

Component layout from page 22, Circuit drawing from page 25

Interlocking pin

	Typ-Nr.	
Interlocking pin	71-679.0	0.001



Illumination

Filament lamp

	Socket	Operating voltage/-current	Typ-Nr.	
Filament lamp	T1 $\frac{3}{4}$ MG	12 VAC/DC, 75 mA	10-1309.1309	0.001
		14 VAC/DC, 80 mA	10-1310.1319	0.001
		18 VAC/DC, 40 mA	10-1311.1249	0.001
		24 VAC/DC, 35 mA	10-1312.1229	0.001
		28 VAC/DC, 30 mA	10-1313.1209	0.001
		28 VAC/DC, 40 mA	10-1313.1249	0.001
		36 VAC/DC, 20 mA	10-1316.1179	0.001
		36 VAC/DC, 30 mA	10-1316.1209	0.001
		48 VAC/DC, 20 mA	10-1319.1179	0.001
		48 VAC/DC, 25 mA	10-1319.1199	0.001
		6 VAC/DC, 120 mA	10-1306.1349	0.001
		6.3 VAC/DC, 200 mA	10-1307.1369	0.001

