



SEMIPACK® 1

Thyristor / Diode Modules


SKKT 106
SKKT 106B
SKKH 106
Features

- Heat transfer through aluminium oxide ceramic isolated metal baseplate
- Hard soldered joints for high reliability
- UL recognized, file no. E 63 532

Typical Applications

- DC motor control (e. g. for machine tools)
- AC motor soft starters
- Temperature control (e. g. for ovens, chemical processes)
- Professional light dimming (studios, theaters)

¹⁾ See the assembly instructions



V_{RSM}	V_{RRM} , V_{DRM}	$I_{TRMS} = 180 \text{ A}$ (maximum value for continuous operation)		
V	V	$I_{TAV} = 106 \text{ A}$ (sin. 180; $T_c = 85 \text{ }^\circ\text{C}$)		
900	800	SKKT 106/08E	SKKT 106B08E	SKKH 106/08E
1300	1200	SKKT 106/12E	SKKT 106B12E	SKKH 106/12E
1500	1400	SKKT 106/14E	SKKT 106B14E	SKKH 106/14E
1700	1600	SKKT 106/16E	SKKT 106B16E	SKKH 106/16E
1900	1800	SKKT 106/18E	SKKT 106B18E	SKKH 106/18E

Symbol	Conditions	Values	Units
I_{TAV}	sin. 180; $T_c = 85 (100) \text{ }^\circ\text{C}$	106 (78)	A
I_D	P3/180F; $T_a = 35 \text{ }^\circ\text{C}$; B2 / B6	145 / 180	A
	P16/200F; $T_a = 35 \text{ }^\circ\text{C}$; B2 / B6	190 / 260	A
I_{RMS}	P3/180F; $T_a = 35 \text{ }^\circ\text{C}$; W1 / W3	200 / 3 * 140	A
I_{TSM}	$T_{vj} = 25 \text{ }^\circ\text{C}$; 10 ms	2250	A
	$T_{vj} = 130 \text{ }^\circ\text{C}$; 10 ms	1900	A
i^2t	$T_{vj} = 25 \text{ }^\circ\text{C}$; 8,3 ... 10 ms	25000	A ² s
	$T_{vj} = 130 \text{ }^\circ\text{C}$; 8,3 ... 10 ms	18000	A ² s
V_T	$T_{vj} = 25 \text{ }^\circ\text{C}$; $I_T = 300 \text{ A}$	max. 1,65	V
$V_{T(TO)}$	$T_{vj} = 130 \text{ }^\circ\text{C}$	max. 0,9	V
r_T	$T_{vj} = 130 \text{ }^\circ\text{C}$	max. 2	m•
I_{DD} ; I_{RD}	$T_{vj} = 130 \text{ }^\circ\text{C}$; $V_{RD} = V_{RRM}$; $V_{DD} = V_{DRM}$	max. 20	mA
t_{gd}	$T_{vj} = 25 \text{ }^\circ\text{C}$; $I_G = 1 \text{ A}$; $di_G/dt = 1 \text{ A}/\mu\text{s}$	1	μs
t_{gr}	$V_D = 0,67 * V_{DRM}$	2	μs
$(di/dt)_{cr}$	$T_{vj} = 130 \text{ }^\circ\text{C}$	max. 150	A/ μs
$(dv/dt)_{cr}$	$T_{vj} = 130 \text{ }^\circ\text{C}$	max. 1000	V/ μs
t_q	$T_{vj} = 130 \text{ }^\circ\text{C}$	100	μs
I_H	$T_{vj} = 25 \text{ }^\circ\text{C}$; typ. / max.	150 / 250	mA
I_L	$T_{vj} = 25 \text{ }^\circ\text{C}$; $R_G = 33 \text{ }^\bullet$; typ. / max.	300 / 600	mA
V_{GT}	$T_{vj} = 25 \text{ }^\circ\text{C}$; d.c.	min. 3	V
I_{GT}	$T_{vj} = 25 \text{ }^\circ\text{C}$; d.c.	min. 150	mA
V_{GD}	$T_{vj} = 130 \text{ }^\circ\text{C}$; d.c.	max. 0,25	V
I_{GD}	$T_{vj} = 130 \text{ }^\circ\text{C}$; d.c.	max. 6	mA
$R_{th(j-c)}$	cont.; per thyristor / per module	0,28 / 0,14	K/W
$R_{th(j-c)}$	sin. 180; per thyristor / per module	0,3 / 0,15	K/W
$R_{th(j-c)}$	rec. 120; per thyristor / per module	0,32 / 0,16	K/W
$R_{th(c-s)}$	per thyristor / per module	0,2 / 0,1	K/W
T_{vj}		- 40 ... + 130	$^\circ\text{C}$
T_{stg}		- 40 ... + 125	$^\circ\text{C}$
V_{isol}	a. c. 50 Hz; r.m.s.; 1 s / 1 min.	3600 / 3000	V~
M_s	to heatsink	$5 \pm 15 \%$ ¹⁾	Nm
M_t	to terminal	$3 \pm 15 \%$	Nm
a		$5 * 9,81$	m/s ²
m	approx.	95	g
Case	SKKT	A 46	
	SKKT ...B	A 48	
	SKKH	A 47	