



ORION FANS

Standard and Custom Cooling Solutions with JIT Delivery Worldwide


SPECIFICATION

Click anywhere on the page below to download the pdf

CORDS



3-conductor & Custom Power Cords



International Power Cords & Connectors

Shielded & Unshielded

Hospital Grade



Custom Fan Assemblies & Connectors

2 & 3-conductor

Molded Plugs



Example: 3-conductor, unshielded, SJT cord with a 5-15P plug and a C-13 connector. 6'7" long, black



No. of Conductors	Wire Gauge	Cord Type	Plug	Connector	Length	Color Code
2	4	1	3	1	67	01
1 = 2 Conductor	2 = 12AWG	1 = SJT	0 = None	0 = None	18 = 1'8"	01 = Black
2 = 3 Conductor	4 = 14AWG	2 = SVT	1 = 1-15 Standard	1 = C-13 Straight	33 = 3'3"	02 = Brown
(unshielded)	6 = 16AWG	3 = SPT-1	2 = 1-15P Polarized	2 = C-13 Right	50 = 5'0"	03 = Gray
3 = 3 Conductor	8 = 18AWG	4 = SJO	3 = 5-15P Straight	Angle	60 = 6'0"	05 = White
(shielded)	A = 0.75mm	6 = H03VV-F	4 = 5-15P Right Angle	3 = C-14	67 = 6'7"	
			5 = 5-15P Hospital	4 = C-15	76 = 7'6"	

B = 1.0mm 7 = H03VVH2-F
 C = 1.5mm 8 = H05VV-F

**LET US QUOTE ON
 YOUR CUSTOM CORD
 REQUIREMENTS**

Grade Clear
 6 = 5-15P Hospital
 Grade Gray
 7 = C-14
 8 = 5-20P
 9 = 6-15P
 A = 003A Europe
 B = 006B Europe
 C = 010 Europe
 D = 010A Europe
 E = 012A UK
 F = 015 Australia
 G = 019 Europe

5 = C-19 80 = 8'0"
 6 = C-17 910 = 9'10"
 7 = 022A 100 = 10'0"
 8 = 002-2 160 = 16'0"

**COMPLETE TURNKEY
 ASSEMBLIES DELIVERED
 JIT WORLDWIDE**

STOCKED CORDS						
Part No.	Wire Gauge (AWG)	Cord Type	Plug	Connector		
24130-67-01	14	SJT	5-15P	wire leads		
24130-910-01						
26130-67-01	16					
26130-910-01						
28130-67-01	18	SVT				
28130-910-01						
28230-67-01	14	SJT			C-14	C-13
28230-910-01						
24131-67-01	16					
24131-910-01						
26131-67-01	18		SVT			
26131-910-01						
28131-67-01	16		SJT	C-14		
28131-910-01						
28231-76-01	18	SVT				
26171-33-01						
28171-33-01	16	SJT	none			
28271-33-01						
26101-67-01	18	SVT				
26101-910-01						
28101-67-01	16	SJT	none			
28101-910-01						
28201-76-01	18	SVT				

CORDAGE	DESCRIPTION
SPT-1	Service Parallel Thermoplastic, 1/32" Insulation, 2 or 3 conductor
SPT-2	Service Parallel Thermoplastic, 3/64" Insulation, 2 or 3 conductor
SPT-3	Service Parallel Thermoplastic, 1/16" Insulation, 2 or 3 conductor
SJT	Service Junior Thermoplastic, 3 conductor
SVT	Service Vacuum Thermoplastic, 3 conductor
SJO	Service Junior Oil Resistent, 3 conductor
SJTW-A	Service Junior Thermoplastic, Outdoor use, 3 conductor
HPN	Heater Parallel Neoprene, 2 or 3 conductor
H03VV-F	Harmonized, 300V, PVC jacket and conductor insulation, flexible cable
H03VVH2-F	Harmonized, 300V, PVC jacket and conductor insulation, flat, non-separable
H05VV-F	Harmonized, 500V, PVC jacket and conductor insulation, flexible cable