

POWER TRANSFORMERS

Single Secondary

Style A



Style NV



Style C



All Primaries 50/60 Hz.

| Sec. | STANCOR PART NUMBER | Primary Volts | Secondary Volts | Amps. | Style | Insulation Test RMS Volts | Termination | | DIMENSIONS-INCHES | | | | | Weight (lbs.) | Agency Certification |
|------|---------------------|---------------|-----------------|-------|-------|---------------------------|-------------|-------|-------------------|------|------|--------|------|---------------|----------------------|
| | | | | | | | | | Pri. | Sec. | H | Case W | D | | |
| A | P-8130 | 117 | 12.6 C.T. | 2.00 | A | 1500 | Leads | Leads | 2.00 | 3.25 | 2.13 | 2.81 | - | 1.40 | |
| | P-8715 | 230 | 12.6 C.T. | 2.00 | A | 1500 | Leads | Leads | 2.00 | 3.25 | 2.13 | 2.81 | - | 1.40 | - |
| | P-8358 | 117 | 12.6 C.T. | 3.00 | A | 1500 | Leads | Leads | 2.38 | 3.75 | 2.25 | 3.13 | - | 1.60 | - |
| | P-8641 | 117 | 12.6 C.T. | 4.00 | A | 1500 | Leads | Leads | 2.62 | 4.00 | 2.38 | 3.56 | - | 2.30 | - |
| B | P-8644 | 117 | 12.6 C.T. | 10.0 | C | 1500 | Leads | Leads | 4.25 | 3.44 | 3.38 | 2.75 | 2.69 | 6.30 | - |
| | P-8553 | 115 | 14.0 C.T. | 0.25 | A | 1500 | Leads | Leads | 1.38 | 2.38 | 1.44 | 2.00 | - | 0.40 | - |
| | P-8555 | 115 | 14.0 C.T. | 1.00 | A | 1500 | Leads | Leads | 2.00 | 3.25 | 1.75 | 2.81 | - | 1.20 | - |
| | P-8557 | 115 | 14.0 C.T. | 4.00 | NV | 1500 | Leads | Leads | 3.00 | 2.56 | 2.44 | 2.00 | 2.25 | 3.00 | - |
| C | P-8558 | 115 | 14.0 C.T. | 6.00 | NV | 1500 | Leads | Leads | 3.50 | 2.81 | 2.88 | 2.25 | 2.38 | 4.00 | - |
| | P-8691 | 115 | 18.0 C.T. | 1.00 | A | 1500 | Leads | Leads | 2.00 | 3.31 | 2.13 | 2.81 | - | 1.50 | - |
| | P-8692 | 115 | 18.0 C.T. | 1.50 | A | 1500 | Leads | Leads | 2.38 | 3.75 | 2.13 | 3.13 | - | 1.70 | - |
| | P-8693 | 115 | 18.0 C.T. | 2.00 | A | 1500 | Leads | Leads | 2.38 | 3.75 | 2.25 | 3.13 | - | 2.00 | - |
| D | P-8504 | 115/230 | 20.0 C.T. | 0.25 | A | 2500 | Leads | Leads | 1.44 | 2.38 | 1.38 | 2.00 | - | 0.40 | - |
| | P-8505 | 115/230 | 20.0 C.T. | 0.30 | A | 2500 | Leads | Leads | 1.44 | 2.38 | 1.38 | 2.00 | - | 0.60 | - |
| | P-8507 | 115/230 | 20.0 C.T. | 0.50 | A | 2500 | Leads | Leads | 1.75 | 2.88 | 1.63 | 2.38 | - | 0.80 | - |
| | P-8508 | 115/230 | 20.0 C.T. | 1.00 | A | 2500 | Leads | Leads | 2.00 | 3.25 | 2.25 | 2.81 | - | 1.40 | - |
| E | P-8604 | 117 | 20.0 C.T. | 1.00 | A | 1500 | Leads | Leads | 2.00 | 3.25 | 2.13 | 2.81 | - | 1.40 | |
| | P-8559 | 115 | 20.0 C.T. | 2.00 | A | 1500 | Leads | Leads | 2.56 | 4.00 | 2.25 | 3.56 | - | 2.50 | - |
| | P-8560 | 115 | 20.0 C.T. | 4.00 | NV | 1500 | Leads | Leads | 3.50 | 2.81 | 3.06 | 2.25 | 2.06 | 4.00 | - |
| | P-8551 | 115 | 24.0 | 1.00 | A | 1500 | Leads | Leads | 1.94 | 3.25 | 2.13 | 2.81 | - | 1.40 | - |
| F | P-8694 | 115 | 24.0 | 2.00 | A | 1500 | Leads | Leads | 2.63 | 4.00 | 2.00 | 3.56 | - | 2.30 | - |
| | P-8394 | 117 | 24.0 C.T. | 0.085 | A | 1500 | Leads | Leads | 1.25 | 2.13 | 1.25 | 1.75 | - | 0.25 | - |
| | P-8395 | 117 | 24.0 C.T. | 0.20 | A | 1500 | Leads | Leads | 1.38 | 2.38 | 1.38 | 2.00 | - | 0.35 | |
| | P-8721 | 230 | 24.0 C.T. | 0.20 | A | 1500 | Leads | Leads | 1.38 | 2.38 | 1.38 | 2.00 | - | 0.35 | - |
| G | P-8578 | 115/230 | 24.0 C.T. | 0.20 | A | 1500 | Leads | Leads | 1.38 | 2.38 | 1.50 | 2.00 | - | 0.30 | - |
| | P-8396 | 117 | 24.0 C.T. | 0.40 | A | 1500 | Leads | Leads | 1.75 | 2.88 | 1.63 | 2.38 | - | 0.60 | |
| | P-8722 | 230 | 24.0 C.T. | 0.40 | A | 1500 | Leads | Leads | 1.75 | 2.88 | 1.63 | 2.38 | - | 0.60 | - |
| | P-8397 | 117 | 24.0 C.T. | 0.70 | A | 1500 | Leads | Leads | 2.00 | 3.25 | 1.75 | 2.81 | - | 0.85 | |
| H | P-8723 | 230 | 24.0 C.T. | 0.70 | A | 1500 | Leads | Leads | 2.00 | 3.25 | 1.75 | 2.81 | - | 0.85 | - |
| | P-8661 | 117 | 24.0 C.T. | 1.00 | A | 1500 | Leads | Leads | 2.00 | 3.25 | 2.06 | 2.81 | - | 1.40 | |
| | P-8575 | 115/230 | 24.0 C.T. | 1.00 | A | 1500 | Leads | Leads | 2.00 | 3.25 | 2.06 | 2.81 | - | 1.30 | |
| | P-8662 | 117 | 24.0 C.T. | 2.00 | A | 1500 | Leads | Leads | 2.62 | 4.00 | 2.38 | 3.56 | - | 2.30 | - |
| I | P-8663 | 117 | 24.0 C.T. | 4.00 | NV | 1500 | Leads | Leads | 3.88 | 3.19 | 2.81 | 2.50 | 2.13 | 4.00 | |
| | P-8664 | 117 | 24.0 C.T. | 6.00 | NV | 1500 | Leads | Leads | 4.19 | 3.44 | 3.00 | 2.75 | 2.25 | 5.70 | - |
| | P-8665 | 117 | 24.0 C.T. | 8.00 | NV | 1500 | Leads | Leads | 4.19 | 3.44 | 3.38 | 2.75 | 2.75 | 7.30 | - |
| | P-8695 | 115 | 24.0 C.T. | 10.0 | NV | 1500 | Leads | Leads | 4.31 | 3.44 | 3.50 | 2.75 | 3.13 | 8.00 | - |

* Agency Certification Note: UL Recognized (File E68100, Guide #XPTQ2)