

## HBL7464V -- Twist-Lock Valise Connector Body



2P2W, 15A 125V, ML-1R, Black Nylon


### Product Specifications

#### Product Type



<b>Product Item</b>	Plug
<b>Wiring Scheme</b>	2 Pole, 2 Wire Non-Grounding
<b>Amperage</b>	15A
<b>Voltage</b>	125V AC
<b>NEMA Configuration</b>	ML-1P
<b>Item Style</b>	Valise
<b>Device Color</b>	Black
<b>Cord Dia.</b>	.218"-.375" (5.5-9.5)
<b>Housing Material</b>	Black nylon
<b>Terminal Clamp Material</b>	Cold rolled steel-nickel-plated
<b>Terminal Screw Material</b>	#8-32 Steel (copper flash, nickel plate & molykote)
<b>Cord Clamp Screw Material</b>	Steel - zinc plated Multi-drive
<b>Body Holding Screw Material</b>	Steel, zinc plated Multi-drive
<b>Ratings</b>	Molded into face

<b>Dielectric Voltage Withstand</b>	2,000V minimum
<b>Current Interrupting</b>	Certified for current interrupting at full rated current.
<b>Temperature Rise</b>	Max 30C temperature rise at full rated current after 50 cycles of overload at 150% of rated current at a power factor of .75.
<b>Cord Accommodation</b>	Round portable service cords of diameters commensurate with the device rating as defined in UL Standard 62, CSA C22.2 No. 49.
<b>Terminal Accommodation</b>	15A #14AWG
<b>Terminal Identification</b>	Terminals identified in accordance with UL 498 (X, Y, Z, White, )
<b>Flammability</b>	HB or better per UL 94 or CSA 22.2 No. 0.6
<b>Operating Temperatures</b>	Maximum Continuous 75 C Minimum -40 C (w/o impact)
<b>Moisture Resistance</b>	IP20
<b>Listings</b>	UL
<b>Catalog Page</b>	<a href="#">Click here for catalog page B2</a>
<b>Brochures</b>	<a href="#">Click here for product brochure</a>
<b>Hubbellnet</b>	<a href="#">Click here for Hubbellnet</a>
<b>Catalog Section</b>	<a href="#">Click here for Section-B</a>
<b>UPC Number</b>	78358523725
<b>Weight in LBS</b>	0.1




## TWIST-LOCK® Devices


### 2 Pole, 2 Wire, Non-Grounding

15 Ampere, 125 Volts

#### Midget TWIST-LOCK Flanged Receptacle, Plug, Connector Body and Flanged Inlet




**HBL7468**



**HBL7465V**



**HBL7464V**




**HBL7466, HBL7467**



**HBL4890**



**HBL7459V**



#### Flanged Receptacle

Description	Catalog Number
Stainless steel flange, exposed terminals.	<b>HBL7468</b>

#### Male Plug IP20 SUITABILITY

Description	Cord Dia.	Catalog Number
Valise® plug, black nylon.	.220"-.385" (5.6-9.8)	<b>HBL7465V</b>

#### Connector Body IP20 SUITABILITY

Description	Cord Dia.	Catalog Number
Valise connector body, black nylon, polarized.	.220"-.385" (5.6-9.8)	<b>HBL7464V</b> -

#### Flanged Inlets

Description	Catalog Numbers
Stainless steel flange, polarized, exposed terminals.	- <b>HBL7467</b>
Stainless steel flange, not polarized, exposed terminals.	- <b>HBL7466</b>

#### Weatherproofing Accessories

Description	Catalog Numbers
Seal-tite® cover, black elastomer, for use with a HBL7465V when used with a HBL7464V connector body or a HBL7464V connector when used with a flanged inlet.	<b>HBL7490V**</b> *
Seal-tite cover, black elastomer, for use with a HBL7464V connector body and combination of HBL7465V plug and HBL7490V cover.	<b>HBL7459V**</b> *
Closure cover for use with HBL7466 or HBL7467. Bead chain is nickel-plated.	<b>HBL4890</b> *

\*\* IP55 suitability when installed and used properly with plug and connector

body combinations.

\* Not UL Listed.



**HBL7490V**