

SEARCH OUR PRODUCTS


aluminum electrolytic & organic semiconductor


film


power film

 
tantalum ceramic



Aluminum Electrolytic Capacitors

+105°C Standard Radial Lead Aluminum Electrolytic Capacitors

Part Number: 476CKE063M

[General Specifications \(PDF\)](#)

[Special Order Options](#)

[CKH_CKE document \(PDF\)](#)



Electrical Specifications

Capacitance: 47.0 μ F
Tolerance: -20 %, +20 %
Dissipation Factor: 0.1 at 120 Hz
ESR: 3.527 Ohms at 20° C and 120 Hz
Impedance:
 --
 --

Temperature Range: -55°C to +105°C
WVDC: 63 volts DC
SVDC: 79. volts DC
Leakage Current:
 30.0 μ A after 1 Minute
Ripple Current:
 110.0 mA at 120 Hz and 105°C

Impedance Ratios:

2.0 at -25°C/20°C
 3.0 at -40°C/20°C

Load Life:

2000 Hours at 105°C with 100% of rated voltage and with 0% of rated ripple current

Physical Specifications

Diameter (D): 6.3 mm + 0.5 mm
Length (L): 11.0 mm + 1.5 mm
Lead Wire Diameter (d): 0.5 mm + 0.05 mm
Lead Spacing: 2.5 mm +/- 0.5 mm
Lead Length: 15 mm

