

SEARCH OUR PRODUCTS

aluminum electrolytic & organic semiconductor







TECH TOOLS

tantalum



PRODUCTS | PROFILE | PRESS | EMPLOYMENT | LINKS | CONTACT US | HOME

Aluminum Electrolytic Capacitors

+85°C Standard Axial Lead Aluminum Electrolytic Capacitors



Part Number: 106TTA450M General Specifications (PDF) Special Order Options TTA document (PDF)

Electrical Specifications

Capacitance: 10.0 uF Tolerance: -20 %, +20 %

Dissipation Factor: 0.25 at 120 Hz **ESR:** 41.447 Ohms at 20° C and 120 Hz

Impedance: - and -- and -

Impedance Ratios: 5.0 -25°C/20°C 0.0 -40°C/20°C Load Life:

2000 Hours at 85°C with 100% of rated voltage and with 0% of rated ripple current

Temperature Range: -40°C to +85°C

WVDC: 450 volts DC SVDC: 500. volts DC Leakage Current: 280.0 uA after 1 Minute Ripple Current:

85.0 mA at 120 Hz and 85°C


Physical Specifications

 Diameter (D):
 12.5 mm + 0.8 mm

 Length (L):
 25.0 mm + 2.0 mm

 Lead Wire Diameter (d):
 0.6 mm + 0.05 mm

Lead Length: 35mm





Site Map

View Items in Shopping Cart

Illinois Capacitor, Inc. 3757 West Touhy Avenue Lincolnwood, IL 60712 USA Tel:847.675.1760 Fax:847.673.2850 email:sales@illcap.com

Products | Profile | Press | Employment | Links | Contact | Home | Search by Application | Search by Parameters | Search by Part Number | Search by Competitor Series | Search Distributor Inventory | Search in Diagram View | Tech Center

Site Map | Aluminum Electrolytic | Film | Power Film | Ceramic | Shopping Cart | FAQs | Catalog PDF Files

©Copyright 2003, Illinois Capacitor, Inc. Legal Notices

Illinois Capacitor, Inc. reserves the right to make changes from the specifications herein in the construction and design of its capacitors from time to time without notice. The information and specifications included herein are believed to be accurate and reliable; Illinois Capacitor, Inc. Assumes No Responsibility For Correctness, Specific Application Or Uses. NO WARRANTIES ARE EXPRESSED OR IMPLIED. Illinois Capacitor, Inc. specifically disclaims any implied warranties of merchantability or fitness for any particular purpose.