

SEARCH OUR PRODUCTS


aluminum electrolytic & organic semiconductor


film


power film


tantalum ceramic

TECH TOOLS



Aluminum Electrolytic Capacitors

+105°C High Frequency Low Impedance Radial Lead Aluminum Electrolytic Capacitor



Part Number: 228KXM016M

[General Specifications \(PDF\)](#)

[Special Order Options](#)

[KXM document \(PDF\)](#)

Electrical Specifications

Capacitance: 2,200.0 μ F
Tolerance: -20 %, +20 %
Dissipation Factor: 0.2 at 120 Hz
ESR: 0.151 Ohms at 20° C and 120 Hz
Impedance:
 0.018 Ohms at 20°C 100 kHz
 0.045 Ohms at -10°C 100 kHz

Temperature Range: -40°C to +105°C
WVDC: 16 volts DC
SVDC: 20. volts DC
Leakage Current:
 352.0 μ A after 2 Minutes
Ripple Current:
 2,770.0 mA at 100 kHz and 105°C

Impedance Ratios:

2.0 at -25°C/20°C

3.0 at -40°C/20°C

Load Life:

5000 Hours at 105°C with 100% of rated voltage and with 100% of rated ripple current

Physical Specifications

Diameter (D): 12.5 mm + 0.5 mm
Length (L): 25.0 mm + 2.0 mm
Lead Wire Diameter (d): 0.6 mm + 0.05 mm
Lead Spacing: 5.0 mm +/- 0.5 mm
Lead Length: 15 mm

