

FUSE BLOCKS

DDFL4U - Double Level Fuse Terminal with fuse link on the top level has a separate feed through terminal at the lower level. This eliminates use of an additional feed through terminal.

In DDFL4U(E), specially designed built in circuit gives light indication in the event of a fuse blow out at the top level. The terminal provides separate feed through connection possibility at the lower level.

DDFL4U(LR): This is a modified version of DDFL4U(E) terminal where in two equipotential connection points are available on both ends of the terminal.

Important: The disconnecting device is not suitable for interrupting load. The supply must be switched off before operating the slide link/lever.

† Fuses are sold separately
Altech, see page 34
for details.



COLOR BLOCKS


(other than grey standard)

When ordering please add color suffix to Cat. No.

Example: CTS2.5U-N/R


Color	Ordering Suffix
Red	R
Blue	BU
Black	BL
Orange	O
Green	G
Yellow	Y
White	W
Beige	BG
Dark Brown	DB

DDFL4U



† Fuse not included.

DDFL4U(E)*



† Fuse not included.

	DDFL4U			DDFL4U(E)*		
Terminal Width	8 mm			8 mm		
Height x Length	66 x 88 mm			66 x 88 mm		
Stripping Length	9.5 mm			9.5 mm		
Insulation Material	Polyamide 6.6			Polyamide 6.6		
Type of Connection	4 screw clamps			4 screw clamps		
Fusion Voltage				24V AC/DC, 48V AC/DC, 110V AC/DC, 220V AC		
Type of Fuse Used	Ø5x20, Ø5x25 mm			Ø5x20, Ø5x25 mm		
Approvals						
Wire Range	22-10 AWG	0.5-4 sq.mm	22-10 AWG	22-10 AWG	0.5-4 sq.mm	22-10 AWG
Voltage Rating	600 V	600 V	600 V	600 V	600 V	600 V
Current Rating	Top Level Bottom Level	6.3 A 35 A	6.3 A 32 A	8 A 35 A	6.3 A 32 A	8 A 35 A
Torque	7 lb-in	0.5 Nm	7 lb-in	7 lb-in	0.5 Nm	7 lb-in
	Cat. No.	Std. Pk.		Cat. No.	Std. Pk.	
Terminal Block	DDFL4U	20		DDFL4U(E)*	20	
End Plate	EPDDFL4U	25		EPDDFL4U	25	
DIN Rail <i>for ordering information refer to page 62</i>						
End Stop <i>for ordering information refer to page 63</i>						
Internal Jumper	2 pole 3 pole 4 pole 10 pole		CA729/2 100 CA729/3 50 CA729/4 50 CA729/10 10		CA729/2 100 CA729/3 50 CA729/4 50 CA729/10 10	
Insulated Internal Jumper	2 pole 3 pole 4 pole 10 pole		CA749/2 100 CA749/3 50 CA749/4 50 CA749/10 10		CA749/2 100 CA749/3 50 CA749/4 50 CA749/10 10	
Current Bar	2 pole 3 pole 4 pole 10 pole		CA703/6 100 CA704/6 100 CA705/6 100 CA737/10 100		CA703/6 100 CA704/6 100 CA705/6 100 CA737/10 100	
Shorting Sleeve & Screw			CA707/S/Q/3 100		CA707/S/Q/3 100	
External Jumper	2 pole 3 pole 4 pole 10 pole		CA711/2 100 CA711/3 100 CA711/4 50 CA711/10 25		CA711/2 100 CA711/3 100 CA711/4 50 CA711/10 25	
Marking Tags	(MT Type) (MT Type on Lever)		MT8 100 MT2 100		MT8 100 MT2 100	

*Add required voltage to part number as a suffix. i.e. DDFL4U(E)/24 for 24V AC/DC. ** 25A @ 500 V, 10A @ 690V, 16A @ 500V for fast blow.