


Our commitment. Your advantage.

<u>Home</u> > <u>Products</u> > <u>By Type</u> > <u>Relays</u> > <u>Product Feature Selector</u> > <u>Product Details</u>

# **IAC-5 Product Details**



IAC-5

TE Internal Number: 1393028-4



# Solid State Relays and Input/Output Modules



Converted to EU RoHS/ELV Compliant (Statement of Compliance)

# **Product Highlights:**

- Input/Output Module
- Relay Type = Solid State Input/Output Module
- IAC Series
- Switch Arrangement = 1 Form A (SPST-NO)
- Current Rating = 0.05 Amps.

View all Features

# **Documentation & Additional Information**

#### **Product Drawings:**

None Available

# Catalog Pages/Data Sheets:

• IAC/OAC IDC/ODC Input/Output Modules (PDF, English)

### **Product Specifications:**

None Available

# **Application Specifications:**

None Available

#### Instruction Sheets:

• None Available

# CAD Files: (CAD Format & Compression Information)

- 2D Drawing (DXF, Version B)
- 3D Model (IGES, Version B)
- 3D Model (STEP, Version B)

<u>List all Documents</u>

#### **Additional Information:**

• Product Line Information

# **Additional Product Images:**

- Schematic
- Wiring Diagram

# **Related Products:**

Tooling

# Product Features (Please use the Product Drawing for all design activity)

# **Product Type Features:**

- Product Type = Input/Output Module
- Termination Type = Printed Circuit Terminals
- Housing Style = Industry Standard
- Comment = Minimum Output Current >0 A

# **Electrical Characteristics:**

- Current Rating (Amps.) = 0.05
- Logic Voltage (VDC) = 5
- Output Voltage, Max. (V) = 30
- Output Current, Min. (Amps.) = 0

### **Body Related Features:**

- <u>Series</u> = IAC
- Case Color = Yellow

# **Contact Related Features:**

- Relay Type = Solid State Input/Output Module
- Switch Arrangement = 1 Form A (SPST-NO)
- Output Switching = Random
- Output Type = DC
- Mounting Options = Board Mount
- Approx. Dimensions (L x W x H) (mm [in]) = 43.20 x 15.20 x 31.80 [1.702 x .598 x 1.252]
- Approved Standards = UL Recognized, CSA Certified
- Coupling = Optical

# **Industry Standards:**

- RoHS/ELV Compliance = RoHS compliant, ELV compliant
- <u>Lead Free Solder Processes</u> = Wave solder capable to 240°C, Wave solder capable to 260°C
- RoHS/ELV Compliance History = Converted to comply with RoHS directive

### Other:

• Brand = Potter & Brumfield