


VECTORBORD®PLUGBORD™ PART NO. : 3677-2



Description :

- 4.5" X 6.5" X 0.062, Hole Dia.: 0.042", Grid: 0.100" X 0.100"
- 3-Hole Solder Pads (0.28" x 0.080") for interconnecting multiple component leads
- Holes are not plated-thru.
- Voltage/ground buses interleaved between pad areas on wiring side
- Test point area with solder pads around holes, provided along back edge of board
- Unclad test point area at top of board
- Row and column legends provided
- Layout paper and instructions included..... [Layout Paper\(PDF\)](#)

Circuit Pattern :	3-Hole Solder Pad 1 side only
Contacts :	22/44 @ 0.156" Centers Ni / Gold
16 Pin DIP Capacity :	12
Hole Diameter :	0.042" { 1.0668 mm }
Grid :	0.100" X 0.100" { 2.54mm X 2.54mm }
Dimension { H, W, T } :	4.5" X 6.5" X 0.062"
Material :	FR-4
Wire-Wrap Terminals :	T44, T46, T49 & T68
Solder Connector :	R644
Wire-Wrap Socket Pins :	R32
Wire-Wrap Connector :	R644-3
Extender :	3690
Recommended Card Cage:	CCK 13 Series Card Cage { Subracks }
UL Flammability Class :	94V - 0