



### **PRODUCTS**

Series



**CROSS-REFERENCE** 

Print

# **Screw Connectors for Printed Circuit Boards**

TYPE 930-T (-DS)

3.5 mm spacing - 2 and 3 poles

Download PDF

Distributor Stock Check



**Dovetail Interlocking** Feature



3D Model

Can plug with

compliant

#### **Description**

- Dovetail version
- low profile
- Wire entrance parallel to PC Board
- Can be factory, field or distributor assembled to almost any length


#### **Technical Data**

Center to Center Spacing: 3.5 mm (0.138 in.) **Nominal Cross Section:** 

1 mm<sup>2</sup> (1550 mils<sup>2</sup>)

Wire Stripping Length: 6 mm (0.25 in.) **Recommended Hole Diameter in PC Board:** 

1.2 mm (0.047 in.)



Color specifications

Dimensions: mm (in.)

Length of Connector (L) L = No. of Poles x Center to Center Spacing

When locating connector, allow 0.5 mm clearance around it for process-induced variations.

## **Approval Information**

How to order

UL File No.E69841 CSA File No.LR24322

Rating	Current(A)	Voltage(V)	Application group	AWG
UL	10	300	В	26-16
CSA	7	300	B,E	26-16

<sup>\*</sup> DS version is CSA certified for 26-18 AWG.

### **Screw Tightening Torque:**

UL: 2.0 Ifbin CSA: 0.2 Nm

Rated Impulse Withstand Voltage: 2500 V

### Material

Molding: Polyamide, self extinguishing UL 94, V-0,

color grey

Temperature limits: **Short Time**: 140°C (284°F) Continuous: RTI 105°C (221°F) **Low Limit**: -40°C (-40°F)

**Comparative Tracking Index:** CTI > 600

Oxygen Index Rating: 33%

Top of page

Terminal Body: Tin plated copper alloy

Wire Protector: Nickel silver

Screw: M2, Slotted head, zinc plated blue passivated,

steel substrate

Solder Pin: Ø 0.9 mm (0.035 in.), Tin plated copper

alloy

POLES:

02 and 03

How to order

930-T (-DS) Item

**Options** 

930-T

SM: Special Marking (please provide sketch)

G05: Gold Plating (5 micro inches) G30: Gold Plating (30 micro inches) S30: Silver Plating (30 micro inches)

Note: Plated component: terminal body

WIRE PROTECTOR:

with: - DS

Request sample Request quote

Quantity

**Accessories** 

BST Self Adhesive Marking Strips.

Consecutively numbered.

Add to shopping cart

2008, WECO Electrical Connectors Inc.

ISO 9001 registered quality management system