

Model #: 4SPDX

Waber-by-Tripp Lite Power Strip - Multiple outlet strip with relocatable power tap



Highlights

4 outlets 7.38 in. length Lighted master switch All-metal housing

Description

T applications a wia average of the second s

PLUG/OUTLETS - Input: NEMA 5-15P/Output: 4 NEMA 5-15R

ELECTRICAL - 120VAC, 50/60Hz, 15A (Requires standard NEMA 5-15R wall receptacle)

FORMAT - Corded power distribution strip

Applications

Offers multiple o ideal for distributing alternate waveform UPS or generator power to protected equipment.

Package Includes

4SPDX Power Strip Warranty information Instruction manual

Features

Multi-outlet power strip offers convenient power distribution in workbench, wallmount or floor mount applications Includes 4 NEMA 5-15R output receptacles with 1.520-in. center-to-center spacing Lighted combination power switch with integrated circuit breaker Keyhole mounting support permanent installation on a wide variety of surfaces UL1363 (USA), cUL (Canada) 15A power handling capacity 6-ft. AC line cord

Specifications

SYSTEM OVERVIEW	
Voltage compatibility	120VAC
Frequency compatibility	50/60 Hz
OUTPUT	
Output volt amp capacity (amps)	15A
Outlet quantity / type	4 NEMA 5-15R
Outlet orientation	Single row of 4
Outlet spacing	1.520 in.
INPUT	
Input connection type	NEMA 5-15P
Input cord length (ft.)	6
Input cord length (m)	1.8288
Recommended Electrical Service	15A 120V
LEDS ALARMS & SWITCHES	
Switches	Lighted combination switch / circuit breaker
PHYSICAL	
Unit Dimensions (HWD/in)	7.5 x 2.5 x 1.5
Unit Dimensions (HWD/cm)	19.1 x 6.4 x 3.8
Material of construction	Metal
Integrated keyhole mounting tabs	Keyhole mounting tabs enable mounting to a variety of surfaces
Receptacle Color	Beige
AC line cord color	Beige
CERTIFICATIONS	
UL1363 (Power Tap)	UL1363
cUL / CSA (Canada)	cUL
WARRANTY	
Product warranty	Lifetime