Products & Services

Brands

Technologies

Our Company

Partners & Suppliers

Product Catalog for OH&ES > Cleaning Products and Lubricants > $3M^{TM}$ Chemical Cleaners, Disinfectants and Deodorizers > Industrial Cleaning Products >

3MTM Adhesive Remover 6040, 6.25 fl oz, 6 per case, Restricted



Click to Enlarge Restricted-May be restricted in California. Aerosol cleaner which can dissolve and flush away dirt, grease, tar, most non-curing tape adhesive films, and similar substances. It is a citrus oil based cleaner that emulsifies when flushed with water.

Additional Information

3M ID: 62-4667-2930-8

GTIN(UPC/EAN): 0 00 21200 39296 2

Characteristics:

Name	Value	
Product Form	Can	
Trademark Name 1	3M	



Packaging

3M ID: 62-4667-2930-8

Minimum Order Quantity: 6 CAN

	Imperial	Metric	
Length	6.700 INCH	0.170 MTR	
Width	4.630 INCH	0.118 MTR	
Height	6.840 INCH	0.174 MTR	
Gross Weight	3.0350 LBS	1.3767 KG	



Material Safety Data Sheet

Copyright, 2005, 3M Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: 3M(TM) Adhesive Remover 6040 / 6041 (Aerosol)

MANUFACTURER: 3M

DIVISION: Industrial Adhesives and Tapes

ADDRESS: 3M Center

St. Paul, MN 55144-1000

Issue Date: 09/13/2005 **Supercedes Date:** 12/14/2004

Document Group: 08-6485-0

Product Use:

Specific Use: adhesive remover

SECTION 2: INGREDIENTS

 Ingredient
 C.A.S. No.
 % by Wt

 CITRUS EXTRACT
 8028-48-6
 80 - 90

 PROPANE
 74-98-6
 10 - 20

SECTION 3: HAZARDS IDENTIFICATION

3.1 EMERGENCY OVERVIEW

Odor, Color, Grade: clear, pale yellow, sweet odor

General Physical Form: Gas

Immediate health, physical, and environmental hazards: Closed containers exposed to heat from fire may build pressure and explode. Extremely flammable liquid and vapor. Aerosol container contains flammable material under pressure. May cause allergic skin reaction.

3.2 POTENTIAL HEALTH EFFECTS

Eve Contact:

Moderate Eye Irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

ventilation and/or local exhaust ventilation to control airborne exposures to below Occupational Exposure Limits and/or control mist, vapor, or spray. If ventilation is not adequate, use respiratory protection equipment. Do not use in a confined area or areas with little or no air movement. If exhaust ventilation is not adequate, use appropriate respiratory protection. Provide ventilation adequate to control vapor concentrations below recommended exposure limits and/or control spray or mist.

8.2 PERSONAL PROTECTIVE EQUIPMENT (PPE)

8.2.1 Eye/Face Protection

Avoid eye contact with vapors, mists, or spray.

The following eye protection(s) are recommended: Safety Glasses with side shields.

8.2.2 Skin Protection

Avoid skin contact. Select and use gloves and/or protective clothing to prevent skin contact based on the results of an exposure assessment. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible materials.

8.2.3 Respiratory Protection

Avoid breathing of vapors, mists or spray.

Select one of the following NIOSH approved respirators based on airborne concentration of contaminants and in accordance with OSHA regulations: Half facepiece air-purifying respirator with organic vapor cartridges. Consult the current 3M Respiratory Selection Guide for additional information or call 1-800-243-4630 for 3M technical assistance.

8.2.4 Prevention of Swallowing

Do not eat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water.

8.3 EXPOSURE GUIDELINES

<u>Ingredient</u>	<u>Authority</u>	Type	<u>Limit</u>	Additional Information
PROPANE	ACGIH	TWA	1000 ppm	
PROPANE	OSHA	TWA	1000 ppm	Table Z-1

SOURCE OF EXPOSURE LIMIT DATA:

ACGIH: American Conference of Governmental Industrial Hygienists

CMRG: Chemical Manufacturer Recommended Guideline OSHA: Occupational Safety and Health Administration

AIHA: American Industrial Hygiene Association Workplace Environmental Exposure Level (WEEL)

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Odor, Color, Grade: clear, pale yellow, sweet odor

General Physical Form: Gas

Autoignition temperatureNo Data Available

Flash Point -50.00 °F

Flammable Limits - LEL2.1 % volume [*Details:* CONDITIONS: PROPANE] **Flammable Limits - UEL**2.1 % volume [*Details:* CONDITIONS: PROPANE]

Vapor Density Not Applicable

Vapor Pressure 28 mmHg [@ 20 °C] [Details: Composite Vapor Pressure

(Calculated)]

Page 4 of 8

3M MATERIAL SAFETY DATA SHEET 3M(TM) Adhesive Remover 6040 / 6041 (Aerosol) 09/13/2005

Specific Gravity 0.793 [*Ref Std:* WATER=1]

pH Not ApplicableMelting point No Data Available

Solubility in Water Nil

Evaporation rate No Data Available

Volatile Organic Compounds Approximately 100 % [Test Method: calculated SCAQMD rule

443.1

Percent volatile Approximately 100 % weight

VOC Less H2O & Exempt Solvents Approximately 100 % [Test Method: calculated SCAQMD rule

443.11

Viscosity Not Applicable

SECTION 10: STABILITY AND REACTIVITY

Stability: Stable.

Materials and Conditions to Avoid: Heat

Hazardous Polymerization: Hazardous polymerization will not occur.

Hazardous Decomposition or By-Products

<u>Substance</u> <u>Condition</u>

Aldehydes During Combustion
Hydrocarbons During Combustion
Carbon monoxide During Combustion
Carbon dioxide During Combustion
Ketones Not Specified

SECTION 11: TOXICOLOGICAL INFORMATION

Please contact the address listed on the first page of the MSDS for Toxicological Information on this material and/or its components.

SECTION 12: ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL INFORMATION

Not determined.

CHEMICAL FATE INFORMATION

Not determined.

SECTION 13: DISPOSAL CONSIDERATIONS

Page 5 of 8